Power Up

IP-enabled Episode Hybrid Amplifier

Get premium performance for even the largest outdoor speaker systems with an IP-enabled Episode Amplifier. Its ultra-compact form factor makes it easy to store, but don't let its size fool you – it has enough power to keep your speakers rocking.

Custom DSP Settings

Preconfigured DSP settings ensure this amp pairs perfectly with your Episode® Landscape system. It supports 70V, 8-ohm, and hybrid systems, making it among the most versatile amps available.

Ample Power

Available in 1,000W and 2,000W options, this two-channel amp delivers exceptional sound in spaces big and small.

Hassle-Free

Our intuitive remote management platform lets you reset your device and fix small problems on your own or easily contact your integrator – all from a mobile app.

IP-enabled Episode Hybrid Amplifier		
	EA-AMP-HYB-2D-1000	**EA-AMP-HYB-2D-2000** **(coming soon)**
Channels	2-Channel	2-Channel
Power Output	300W per channel @ 8 ohm (1000W bridged) 500W per channel @ 4 ohm (2000W bridged) 700W per channel @ 2 ohm 500W per channel @ 70V 500W per channel @ 100V (230VAC only)	600W per channel @ 8 ohm (2000W bridged) 1000W per channel @ 4 ohm (2800W bridged) 1200W per channel @ 2 ohm 1000W per channel @ 70V 1000W per channel @ 100V (230VAC only)
Power Consumption	230W Typical 1100W Max	230W Typical 1100W Max
Sensitivity Input	1.4Vrms, max power	1.4Vrms, max power
Impedance Input	RCA Analog input: 10kΩ Balanced Analog input: 20kΩ	RCA Analog input: 10kΩ Balanced Analog input: 20kΩ
Signal to Noise Ratio	101dB A-weighted @ 1.4Vrms & 4Vrms input max	101dB A-weighted @ 1.4Vrms & 4Vrms input max
Total Harmonic Distortion (THD)	Less than 1%	Less than 1%
Frequency Response	± 2dB at 1/8th power (20Hz to 20kHz)	± 2dB at 1/8th power (20Hz to 20kHz)
Inputs	Network: RJ-45 jack, 10/100Mbps	Network: RJ-45 jack, 10/100Mbps
Audio Inputs / Outputs	Bal. Analog Audio: 2x 3-pos. Phoenix-style pluggable screw term. block Analog RCA: White jack (L Ch), Red jack (R Ch) Spkr. Output: 2x 3 pos. Phoenix-style pluggable screw term. block (12-18 AWG)	Bal. Analog Audio: 2x 3-pos. Phoenix-style pluggable screw term. block Analog RCA: White jack (L Ch), Red jack (R Ch) Spkr. Output: 2x 3 pos. Phoenix-style pluggable screw term. block (12-18 AWG)
12V Trigger	90 dB	90 dB
Dimensions (W x H x D)	17" x 1.75" x 12"	17" x 1.75" x 12"
Rack Spacing	1U	1U
Weight	12 lb	12 lb