

MODEL SB-4217HD

DISPLAY

AVAILABLE COLORS





Black



Shown in Black

KEY FEATURES

- 42" Pro Series True-Outdoor All-Weather Television for permanent outdoor installation
- Landscape Orientation only, use DS-4217P for portrait installation.
- Ultra-Bright (700 NIT) 42-inch full HD, 1080p LED screen for improved outdoor viewing
- Direct Sunlight-Readable
- Anti-glare protective glass and removable front bezel for easy field servicing
- Massive, side-opening cable/media bay provides easy access (Opening: 6.45" x 13.5" x 3.0" deep / Interior: 7.9" x 17.7" x 2.1" deep)
- Media bay power port powers media players without the need for external cords (5v@3.5amps / 12v@3amps)
- Side-mounted cable ports for improved access and visibility
- High temperature Enhanced Solar Tolerance (EST) technology prevents isotropic blackout
- Thermal-flow air ventilation system keeps the unit cool & dry in temperatures up to 122
 degrees F
- Ability to operate in cold weather (-40 degrees F)
- Exterior designed to protect internal components from rain, snow, dust, insects, humidity, and salt air
- Powder-coated rust-proof aluminum exterior for strength and durability
- RS232 serial control with discrete on, off, and input control (located in the cable-entry compartment)
- Rear IR receiver (located in the cable-entry compartment)
- Innovative water-tight Cable Entry System seals out moisture and allows for easy hook-ups
- Weatherproof detachable 20W speaker bar (Top or bottom mount)
- Quick-change filtration cartridges
- Weatherproof remote control
- Weatherproof control buttons with optional tamper-proof plate
- Remote control Lock-out prevents unauthorized users from changing the programming
- Includes Weatherproof Detachable 20W Speaker Bar, Weatherproof Remote Control, Warranty, and Manual



MODEL SB-4217HD

SCREEN

SCREEN

42-inch Diagonal Color Active Matrix

TFT LED

RESOLUTION

1920 x 1080 Full-HD 1080p

ASPECT RATIO

16:9

CONTRAST RATIO

1300:1

FRAME RATE

120 Hz

VIEWING ANGLE

178° x 178°

RESPONSE TIME

12 milliseconds

TV FORMATS

1080p, 1080i, 720p, 720i, 480p, 480i

CONNECTIONS

RF

Antenna/CATV (ATSC/QAM/NTSC) x1

HDMI

HDMI™ Input x2

VIDEO COMPOSITE

S-Video x1 or Composite Video x1, L/R

Audio Inputs x1

VIDEO COMPONENT

YPbPr plus Stereo Audio x2

PC-VGA

15-pin D-sub VGA plus Stereo Audio

CONTROL SET

RS232 Serial, Discrete IR Control,

Concealed rear IR Window

AUDIO OUT

Digital SPDIF Audio(Fixed)

Analog 1/8" headphone jack (Variable)

SPEAKERS

20 WATT detachable speaker bar (top

or bottom mount)

INPUT POWER

100-240 VAC, 50-60 Hz 2.0 A @ 120v

Max (1.25 A @ 120v)

TEMPERATURE TOLERANCES

OPERATING TEMP

-40° to 122° F. (-40° to 50°C.)

NON-OP. TEMP

-40° to 140° F. (-40° to 60°C.)

(OFF MODE WITH POWER APPLIED)

The non-operating temperature feature requires power to be applied.

PHYSICAL SPECS

ACCESSORIES INCLUDED

Weatherproof remote control, top or bottom

mount speaker bar

EXTERIOR

Powder-coated aluminum

EXTERIOR COLORS

Black, Silver, & White

TV DIMENSIONS

39.43in W x 23.41in H (26.41in H with speakers) x

5.57in D

1002mm W x 595mm H (667mm H with speakers)

x 141mm D

VESA MOUNT PATTERN

400mm x 400mm

TV WEIGHT

55lbs/25kg (59lbs/26.8kg with speaker)

SHIPPING DIMENSIONS

TBE

SHIPPING WEIGHT

69 lbs/31.3kg

RESIDENTIAL WARRANTY

Two-year parts and labor

COMMERCIAL WARRANTY

Two-year parts and labor