



WattBox® 900 Series IP Power Conditioner with Series Mode Surge Protection

When uptime is critical, this IP power conditioner delivers. In a full 1U rack-mount form factor, it combines non-sacrificial Surge Elimination Circuit (SEC) technology with twelve individually controlled and metered outlets, full OvrC integration, and the Power Insights Dashboard, giving integrators the visibility and remote management needed to keep systems running without unnecessary service calls. Backed by a six-year warranty, it's built for long-term reliability that doesn't degrade with multiple surges.

WB-900-SEC-IPVM-12

EMI/RFI Filtration	# of Filters = 1 for 12 outlets
Outlets	(12) NEMA 5-15R Outlets
Safe Voltage	Yes, (90V ~ 136V)
Certifications	UL 62368-1 and CAN/CSA C22.2 No. 62368-1 FCC Part 15 Subpart B / ICES-003 Issue 7 (Class B)
Dimensions	440 mm x 213 mm x 88 mm (17.32 x 8.39 x 3.46 in.)
Features	Protection Modes: L-N, L-G, N-G Locking and Detachable Power Cord
Inputs	AC Input Connection: IEC C-14, with integrated fuse holder
Operating Temperature	14 to 104°F (-10 to 40°C)

Power Cord Length	2m (6.6 ft.) 14AWG C13
Line Voltage	120V, 50/60 Hz
Fuse Rating	15A
UL Current Rating	12A
UL Power Rating	1500W
Rack Spacing	2U
Fuse Type	Fast-acting ceramic tube fuse
IP Controllable Outlets	12
API	Yes
Power Metering	Individual Outlets: Yes, Whole Device: Yes
Surge Protection	Yes, non-sacrificial (L-N)