
16/4 RISER RATED, UNSHIELDED SECURITY & CONTROL CABLE

16 AWG 4 Stranded Conductors

Ratings	CMR, CL3R, FT4
Approvals	ETL Listed



Construction

Conductor	16 AWG 19 Strand Bare Copper
Conductor Count	4
Insulation	PVC (0.011" nom.)
Insulation Colors	Black, Red, White, Green
Lay Length	5.25" nom.
Shielding	N/A
Rip Cord	Yes
Jacket	PVC (0.016" nom.)
Overall Diameter	0.205" nom.
Print Legend	ADI PRO P/N RN-XXXX OXYGEN FREE 4C16 3180662 C(ETL)US CL3R 75C, CMR FT4 RoHS LOT#XXXX MMDDYY XXXXFT

Properties

Operating Voltage	300 Volts max.
DC Resistance	4.19 Ohms/1000' at 20°C
Capacitance	23.2 pF/ft. nom.
Temperature	-20°C to 60°C
Flame Rating	UL 1666 (Riser); CSA C22.2 No. 2556 (FT4)
RoHS Compliant	Yes
Country of Origin	CHINA

PART#	COLOR	LENGTH	BOX
RN-83SR509	GREY	500FT	EXPRESS BOX

RoHS COMPLIANT

Intertek

For more information contact your ADI Sales person or visit adiglobal.com/adiexclusivebrands