Plug-in Power Adapter

12VDC, 2A, Screw Terminal

0E-PPS12V2AS



PRODUCT DESCRIPTION

0E-PPS12V2AS is a fully regulated 12VDC, 2A plug-in switching adapter with screw terminal output that provides reliable DC power for a wide variety of indoor security and surveillance products and applications. It can be used with input voltage ranging from 100 to 240VAC and includes a power indicator LED. Self-limiting protection against short circuit and overload conditions is included, with auto-recovery. Complies with DOE Level VI Efficiency and FCC requirements.

FEATURES

- 12VDC, 2A (24W)
- Primary: 100 to 240VAC, 50/60Hz, 0.8A
- I.T.E. power supply
- Short circuit and overload protected; auto-recovery
- Power indicator LED
- 3-prong adapter with three screw terminals including ground
- Efficiency Level VI, FCC compliant and UL Listed
- For indoor use only



SPECIFICATIONS

PART#	0E-PPS12V2AS
UPC	811914026129
PRIMARY	100 to 240VAC, 50/60Hz, 0.8A
SECONDARY	12VDC, 2A (24W)
SHORT/OVERLOAD PROTECTION	Auto-recovery
OPERATING TEMPERATURE	32°F to 113°F (0°C to 45°C)
DIMENSIONS (L x W x H)	1.6" x 2.2" x 4.3" (41 x 56 x 109mm)
WEIGHT	4.3 oz. (122g)











