

TRIAD[®]

Cinema Subwoofers



Performance Above All Else

Triad Cinema Subwoofers are designed for high-output applications and to bring the incredible, dynamic sound found in theaters to your customer's home. As a 4-Ohm subwoofer, they provide compact, higher-quality sound for a more immersive home theater experience.

Improved Visual Design

Say goodbye to the "little black box in the corner" with a new industrial design that's perfect for both behind-the-screen and in-room installations. These subwoofers boast a sleek, modern look and feel that seamlessly integrates into any environment.

- Integrated front wiring for easy access without un-mounting
- Built-in handles for safer, easy lifting
- Rubber isolation bumpers for an improved listening experience in the intended space
- Heavy duty binding posts for stronger connections and improved performance
- Mounting space at 16" for alignment with drywall studs

Individual Product Specifications	TS-PAS12-4	TS-PAS15-4	TS-PAS18-4	TS-PAS18DVC-4
Dimensions (W x H x D)	16" x 26.5" x 10.5" 406.4mm x 673.1mm x 266.7mm	19.5" x 28" x 11.75" 495.3mm x 711.2mm x 298.5mm	24.75" x 34" x 12.75" 628.7mm x 863.6mm x 323.9mm	24.75" x 34" x 12.75" 628.7mm x 863.6mm x 323.9mm
Weight	31.8kgs / 70lbs	41.7kgs / 92lbs	61.24kgs / 135lbs	61.24kgs / 135lbs
Woofer Count	1	1	1	1
Woofer Size / Material	Fiber Damped Aluminum	Fiber Damped Aluminum	18" / Engineered Composite Fiber Cone	18" / Engineered Composite Fiber Cone
Woofer Magnet Type	Ferrite	Ferrite	Neodymium	Neodymium
Voice Coil Diameter	64mm	64mm	100mm	100mm
Enclosure Type	Sealed	Sealed	Sealed	Sealed
Connector Type	5-Way Binding Posts	5-Way Binding Posts	5-Way Binding Posts	5-Way Binding Posts
Power Handling (RMS)	700 W	800 W	1200 W	2x1200 W
Peak Power Handling	1400 W	1600 W	2400 W	2x2400 W
Sensitivity 2.83V@1m	94 dB	98 dB	101 dB	104 dB
Nominal Impedance	4 Ohm	4 Ohm	4 Ohm	2 x 4 Ohm
Min Impedance (in sealed box)	5.13 Ohm	5.36 Ohm	3.68 Ohm	2 x 3.5 Ohm
Frequency Response (-3dB,) (W/Triad tuning)*	19 Hz - 300 Hz	22 Hz - 300 Hz	23 Hz - 300 Hz	23 Hz- 300 Hz
-6dB LF (W/ Triad tuning)	16 Hz	18 Hz	19 Hz	19 Hz
Xmax	12mm	13.7mm	22.25mm	22.25mm
Gift Box Specifications (Fully packaged with product)	TS-PAS12-4	TS-PAS15-4	TS-PAS18-4	TS-PAS18DVC-4
U of M (Sold as)	Each	Each	Each	Each
Gift Box Dimensions	31.25" x 20.75" x 14.5" 793.8mm x 527.1mm x 368.3mm	32.75" x 24.25" x 15.625" 831.9mm x 616mm x 396.9mm	38.75" x 29.5" x 16.625" 984.3mm x 749.3mm x 422.3mm	38.75" x 29.5" x 16.625" 984.3mm x 749.3mm x 422.3mm
Shipping Weight	31.8kgs / 70lbs	41.7kgs / 92lbs	61.24kgs / 135lbs	61.24kgs / 135lbs