

## VERANDA 4 FULL-SHADE OUTDOOR TV



# SUNBRITE VERANDA 4

## FULL-SHADE OUTDOOR SMART TV

The Veranda 4 delivers 600 nits of 4K60 HDR10 brightness for full-shade outdoor viewing and a vibrant, energy-efficient display. Easy to install, it includes Wi-Fi, Bluetooth (BT5.0), voice control, direct & discreet IR, and IP control for easy integration and seamless performance.

SunBriteTV.com



### A Refined Way to Enjoy the Shade

Deliver premium full shade performance with RGB-W technology on a direct LED backlight screen for brighter pictures and up to 2-4x the brightness of many indoor TVs. The anti-glare screen with Quarter Wave Plate Polarizer (QWP) improves visibility, even if viewers are wearing sunglasses.



### Entertainment Built to Last

With a high operating temperature range, conformal coating on internal components that protect against humidity, and an IP55 rating, this TV can withstand the hottest summer days and almost any storm.



### Streaming Made Easy

Content selection and customization is simple with webOS smart functionality, as well as through the ability to connect almost any streaming device of their choice.

 **SUNBRITE**

	<b>SB-V4-49-BL</b> <i>(Coming Soon)</i>	<b>SB-V4-55-BL</b> <i>(Coming Soon)</i>	<b>SB-V4-65-BL</b>	<b>SB-V4-75-BL</b>
<b>Backlight Compensation</b>	600 nits (cd/m2)	600 nits (cd/m2)	600 nits (cd/m2)	600 nits (cd/m2)
<b>Weatherproof Rating</b>	IP55	IP55	IP55	IP55
<b>VESA Mounting Positions</b>	200×200	400×400	400×400	400×400
<b>Housing</b>	Powder-coated aluminum	Powder-coated aluminum	Powder-coated aluminum	Powder-coated aluminum
<b>Power</b>	GFCI protected 100-240 VAC, 50/60Hz, 4.7A max			
<b>HDMI Connectors</b>	3 inputs (Supports HDMI 2.1, HDMI 2.0, HDM11.4, HDCP 1.4a HDCP 2.2) (eARC on HDMI 2)	3 inputs (Supports HDMI 2.1, HDMI 2.0, HDM11.4, HDCP 1.4a HDCP 2.2) (eARC on HDMI 2)	3 inputs (Supports HDMI 2.1, HDMI 2.0, HDM11.4, HDCP 1.4a HDCP 2.2) (eARC on HDMI 2)	3 inputs (Supports HDMI 2.1, HDMI 2.0, HDM11.4, HDCP 1.4a HDCP 2.2) (eARC on HDMI 2)
<b>Smart TV</b>	webOS	webOS	webOS	webOS
<b>Video Inputs</b>	Composite Video xl, L/R Audio Inputs xl			
<b>Screen Resolution</b>	3840x2160	3840x2160	3840x2160	3840x2160
<b>Back Light</b>	Direct LED	Direct LED	Direct LED	Direct LED
<b>Screen Description</b>	Anti-Glare with Quarter Wave Plate Polarization (QWP) screen RGB-W Tech	Anti-Glare with Quarter Wave Plate Polarization (QWP) screen RGB-W Tech	Anti-Glare with Quarter Wave Plate Polarization (QWP) screen RGB-W Tech	Anti-Glare with Quarter Wave Plate Polarization (QWP) screen RGB-W Tech
<b>Contrast Ratio</b>	1100:1	1100:1	1100:1	1100:1
<b>Frame Rate</b>	60 Hz	60 Hz	60 Hz	60 Hz
<b>Viewing Angle</b>	R/L 178°, U/D 178°			
<b>Response Time</b>	8 milliseconds	8 milliseconds	8 milliseconds	8 milliseconds
<b>TV Formats</b>	2160p (HDMI only), 1080p, 1080i, 720p, 720i, 480p, 480i	2160p (HDMI only), 1080p, 1080i, 720p, 720i, 480p, 480i	2160p (HDMI only), 1080p, 1080i, 720p, 720i, 480p, 480i	2160p (HDMI only), 1080p, 1080i, 720p, 720i, 480p, 480i
<b>Control Set</b>	Direct & Discreet IR control, IP control			
<b>Included Speaker</b>	2 x 8W down firing internal speakers			
<b>Operating Temperature</b>	32° to 122° F. (0° to 50° C)	32° to 122° F. (0° to 50° C)	32° to 122° F. (0° to 50° C)	32° to 122° F. (0° to 50° C)
<b>Non-Operating Temperature</b>	-24° to 140° F. (-31° to 60° C)	-24° to 140° F. (-31° to 60° C)	-24° to 140° F. (-31° to 60° C)	-24° to 140° F. (-31° to 60° C)
<b>Dimensions</b>	44 × 26 × 4.25 in. (1118 × 660 × 108 mm)	49.28 × 28.8 × 4.24 in. (1251.6 × 731.5 × 107.7 mm)	57.89 × 31.85 × 4.23 in. (1470.4 × 808.95 × 107.4 mm)	66.62 × 38.54 × 4.23 in. (1692.1 × 978.9 × 107.4 mm)
<b>Weight</b>	37.0 lb. / 17.0 kg	46.5 lb. / 21.1 kg	59.0 lb. / 26.8 kg	82.9 lb. / 37.6 kg