



# SX-DS-158

## TECHNICAL DESCRIPTION

The SX-DS-158 shall be a one-rack-space unit in a magnetic shielding steel enclosure. It shall operate from 120 volts AC and have a 9-foot, grounded, 3-wire #14 line cord. There shall be 8 grounded AC receptacles on the rear panel. Overall dimensions shall be 1.75" H x 19" W x 8.5" D. Weight shall be 6.5 pounds. The SX-DS-158 shall have a load rating of 15 amps at 120 volts, and provide EMI/RFI filtering, and over voltage shutdown.

SPECIFICATIONS		SX-DS-158
Load Rating		15A
Voltage Rating		120V
Power Requirement (no load)		1 W
EMI/RFI Filter	Normal mode (50Ω load)	>30dB , 70kHz-50MHz
	Common Mode (50Ω load)	> 30dB , 60kHz-30MHz
Under-Voltage Auto Shutdown		No
Over-Voltage Auto Shutdown		180V ± 10V
Over-Current Auto Shutdown		Circuit Breaker
Over-Temperature Auto Shutdown		None
Network Port		No
Serial Port		None
Temperature Sensor Input		None
Auxiliary Relay Outputs		No
Contact Closure Input		No
Dimensions		19" W x 8.5" D x 1.75" H
Weight		6.5 lbs
Temperature Range:		5C to 35C
Humidity Range		5% to 95% R.H. Non-condensing
Agency Listings		Conforms to UL Std 1449 Certified to CSA Std C22.2 No. 8

\* 1.2 x 50 microsecond industry standard combination wave surge as per IEEE C62.41

\*\* Specifications subject to change without notice

SPECS v.022918

