

T5 In-Wall Touchscreen Trim Ring Painting Guide

For use with the Primer (unpainted) trim ring option · T5 8" and 11" models

The paint-ready trim ring allows you to custom-paint the bezel on-site to match any room's painted surfaces. The trim ring has been tested with the paint types below and adheres well when a **compatible surface primer** is used for the paint type.

COMPATIBLE PAINT TYPES

- Oil base acrylic latex
- Water based acrylic latex
- Water based acrylic latex paint + primer combo
- Urethane
- Lacquer
- Automotive polyurethane

BEFORE YOU BEGIN

Primer is required. Paint will not adhere to the plastic surface without a compatible surface primer for the paint type being used.

Remove the trim ring before painting. Do not paint while attached to the touchscreen.

PAINTING PROCESS – FOLLOW IN ORDER

1. Remove trim ring from touchscreen

The magnetic trim ring detaches easily. Set the touchscreen aside in a safe location before proceeding.

2. Clean the trim ring surface

Wipe thoroughly with a solution of **50% water / 50% isopropyl alcohol**. Allow to dry completely.

3. Apply a compatible surface primer

Primer is mandatory. Allow primer to dry per the manufacturer's instructions.

4. Paint

Apply your chosen compatible paint. Follow manufacturer-recommended coats and methods.

5. Allow full dry time, then reattach

Do not reattach until paint is fully cured per manufacturer guidance.

Primer is mandatory

Skipping primer will result in paint failure or peeling

Allow full dry time

Reattachment before cure may bond the trim ring to the touchscreen glass.