

BNC CONNECTORS

COMPRESSION PLUGS



ADI PRO BNC Compression Plugs are designed to facilitate quick, secure termination of coaxial cables while maintaining optimal signal quality. Ideal for HD digital or analog audio and video installations.



FEATURES

Indoor, commercial and residential applications

Terminate raw coaxial cable quickly and securely

Corrosion resistant, with nickel-plated body and gold-plated contact

0E-BNCCOMH75 and 0E-BNCCMH75C boast an improved design for an even tighter connection

Limited Lifetime Warranty

RECOMMENDED TOOLS



0E-BNCCMPTL
Universal Compression Tool
BNC, F and RC



0E-BNCCRTOOL
Universal Crimp Tool
BNC, F, N, TNC, UHFST, SC

Product Specifications

PART #	Cable Type	Imp.	Qty.
0E-BNCCOMPTP	RG59 (PVC) 18-22 AWG	50Ω	10-pk
0E-BNCCOM75T	RG59, RG6 (PVC)	75Ω	10-pk
0E-BNCCOM75C	RG59, RG6 (PVC)	75Ω	100 (jar)
0E-BNCCOMH75	RG59 (PVC) 20 AWG	75Ω	10-pk
0E-BNCCMH75C	RG59 (PVC) 20 AWG	75Ω	100 (jar)

Materials: Nickel-plated zinc (body); Gold-plated brass (contact)



For more information, contact
your ADI salesperson or visit
adiglobal.com/adiexclusivebrands

BNC CONNECTORS

COMPRESSION PLUGS

BNC CONNECTOR	CABLE TYPE	IMPEDANCE	CABLE DIAMETER		FINISH	QTY.	PART #
			DIELECTRIC	JACKET			
Twist-On Plug Male 	RG58 (PVC) RG59 (Plenum) 20-22 AWG	50Ω	.116" - .146"	.195" - .242"	Nickel (body) Gold (contact)	10-pk	0E-BNC59PTOT
	RG59 (PVC) RG6 (Plenum) 18-22 AWG	50Ω	.146" - .185"	.242" - .275"	Nickel (body) Gold (contact)	10-pk	0E-BNCT56PTP
	RG59 (PVC) RG6 (Plenum) 18-22 AWG	75Ω	.146" - .185"	.242" - .275"	Nickel (body) Gold (contact)	10-pk	0E-BNCT5675T
Compression Plug Male   	RG59 (PVC) 18-22 AWG	50Ω	.146"	.242"	Nickel (body) Gold (contact)	10-pk	0E-BNCCOMPTP
	RG59, RG6 (PVC)	75Ω	.146" - .185"	.242" - .275"	Nickel (body) Gold (contact)	10-pk	0E-BNCCOM75T
						10-pk	0E-BNCCOM75C
	RG59 (PVC) 20 AWG	75Ω	.146"	.242"	Nickel (body) Gold (contact)	10-pk	0E-BNCCOMH75
						100 (jar)	0E-BNCCMH75C
Crimp Plug Male  	RG59, RG6 (PVC)	50Ω	.146" - .185"	.242" - .275"	Nickel (body) Gold (contact)	10-pk	0E-BNC2UTP
	RG58 (PVC) RG59, RG6 (PVC or Plenum)	50Ω	.116" - .146" - .185"	.195" - .242" - .275"	Nickel (body) Gold (contact)	10-pk	0E-BNCCRIMPT
						100 (jar)	0E-BNCCRIMPC
	RG58 (PVC) RG59, RG6 (PVC or Plenum)	75Ω	.116" - 0.146" - .185"	.195" - .242" - 0.275"	Nickel (body) Gold (contact)	10-pk	0E-BNCCR75TP
						100 (jar)	0E-BNCCR75C
						10-pk	0E-BNCU75TP
T-Connector Male/2x Female 	--	50Ω	--	--	Nickel (body) Gold (contact)	10-pk	0E-BNCM22FTP
Coupler Female/Female 	--	50Ω	--	--	Nickel (body) Gold (contact)	10-pk	0E-BNCFFTP
	--	75Ω	--	--	Nickel (body) Gold (contact)	10-pk	0E-BNCFF75TP
Adapter BNC Plug/F Jack 	--	75Ω	--	--	Nickel (body) Gold (contact)	10-pk	0E-BNCM22F75
Adapter BNC Jack/RCA Plug 	--	50Ω	--	--	Nickel (body) Gold (contact)	10-pk	0E-BNCFRCAMT

For more information, contact
your ADI salesperson or visit
adiglobal.com/adiexclusivebrands

ADI
PRO