


BNC CONNECTORS

T-CONNECTOR



The ADI PRO BNC T-Connector is designed to split signal from a BNC male plug to two BNC female jacks. The connector is corrosion resistant thanks to a nickel-plated body and a gold-plated center conductor, which also helps to ensure optimal signal for smooth data transfer. Ideal for HD digital or analog audio and video installations.



FEATURES

Indoor, commercial and residential applications

Split signal quickly and securely from a BNC plug (male) to two BNC jacks (female)

Corrosion resistant, with nickel-plated body and gold-plated contact

Limited Lifetime Warranty

RECOMMENDED TOOLS



0E-BNCCMPTL
Universal Compression Tool
BNC, F and RC



0E-BNCCRTOOL
Universal Crimp Tool
BNC, F, N, TNC, UHFST, SC

Product Specifications

PART #: 0E-BNCCM22FTP

UPC: 811914020073

Impedance: 50Ω

Configuration: BNC plug (male) to two BNC jacks (female)

Materials: Nickel-plated zinc (body); Gold-plated brass (contact)

Package Quantity: 10



For more information, contact
your ADI salesperson or visit
adiglobal.com/adiexclusivebrands

BNC CONNECTORS

T-CONNECTOR

BNC CONNECTOR	CABLE TYPE	IMPEDANCE	CABLE DIAMETER		FINISH	QTY.	PART #
			DIELECTRIC	JACKET			
Twist-On Plug Male 	RG58 (PVC) RG59 (Plenum) 20-22 AWG	50Ω	.116" - .146"	.195" - .242"	Nickel (body) Gold (contact)	10-pk	0E-BNC59PTOT
	RG59 (PVC) RG6 (Plenum) 18-22 AWG	50Ω	.146" - .185"	.242" - .275"	Nickel (body) Gold (contact)	10-pk	0E-BNCT56PTP
	RG59 (PVC) RG6 (Plenum) 18-22 AWG	75Ω	.146" - .185"	.242" - .275"	Nickel (body) Gold (contact)	10-pk	0E-BNCT5675T
Compression Plug Male 	RG59 (PVC) 18-22 AWG	50Ω	.146"	.242"	Nickel (body) Gold (contact)	10-pk	0E-BNCCOMPTP
	RG59, RG6 (PVC)	75Ω	.146" - .185"	.242" - .275"	Nickel (body) Gold (contact)	10-pk	0E-BNCCOM75T
						10-pk	0E-BNCCOM75C
	RG59 (PVC) 20 AWG	75Ω	.146"	.242"	Nickel (body) Gold (contact)	10-pk 100 (jar)	0E-BNCCOMH75 0E-BNCCMH75C
Crimp Plug Male 	RG59, RG6 (PVC)	50Ω	.146" - .185"	.242" - .275"	Nickel (body) Gold (contact)	10-pk	0E-BNC2UTP
	RG58 (PVC) RG59, RG6 (PVC or Plenum)	50Ω	.116" - .146" - .185"	.195" - .242" - .275"	Nickel (body) Gold (contact)	10-pk	0E-BNCCRIMPT
						100 (jar)	0E-BNCCRIMPC
	RG58 (PVC) RG59, RG6 (PVC or Plenum)	75Ω	.116" - 0.146" - .185"	.195" - .242" - 0.275"	Nickel (body) Gold (contact)	10-pk	0E-BNCCR75TP
						100 (jar)	0E-BNCCR75C
T-Connector Male/2x Female 	--	50Ω	--	--	Nickel (body) Gold (contact)	10-pk	0E-BNCM22FTP
	--	75Ω	--	--	Nickel (body) Gold (contact)	10-pk	0E-BNCFF75TP
Coupler Female/Female 	--	75Ω	--	--	Nickel (body) Gold (contact)	10-pk	0E-BNCFF75TP
Adapter BNC Plug/F Jack 	--	75Ω	--	--	Nickel (body) Gold (contact)	10-pk	0E-BNCM22F75
Adapter BNC Jack/RCA Plug 	--	50Ω	--	--	Nickel (body) Gold (contact)	10-pk	0E-BNCFRCAMT

For more information, contact
your ADI salesperson or visit
adiglobal.com/adiexclusivebrands

ADI
PRO