

BNC CONNECTORS

TWIST-ON PLUGS



ADI PRO BNC Twist-On Plugs are designed to facilitate quick, secure termination of coaxial cables while maintaining optimal signal quality. Ideal for HD digital or analog audio and video installations.



FEATURES

Indoor, commercial and residential applications

Terminate raw coaxial cable quickly and securely

Corrosion resistant, with nickel-plated body and gold-plated contact

Limited Lifetime Warranty

Product Specifications

PART #	Cable Type	Imp.	Qty.
0E-BNC59PTOT	RG58 (PVC) RG59 (Plen.) 20-22 AWG	50Ω	10-pk
0E-BNCT56PTP	RG59 (PVC) RG6 (Plen.) 18-22 AWG	50Ω	10-pk
0E-BNCT5675T	RG59 (PVC) RG6 (Plen.) 18-22 AWG	75Ω	10-pk

Materials: Nickel-plated zinc (body); Gold-plated brass (contact)

RECOMMENDED TOOLS



0E-BNCCMPTL
Universal Compression Tool
BNC, F and RC



0E-BNCCRTOOL
Universal Crimp Tool
BNC, F, N, TNC, UHFST, SC



For more information, contact
your ADI salesperson or visit
adiglobal.com/adiexclusivebrands

BNC CONNECTORS

TWIST-ON PLUGS

BNC CONNECTOR	CABLE TYPE	IMPEDANCE	CABLE DIAMETER		FINISH	QTY.	PART #
			DIELECTRIC	JACKET			
Twist-On Plug Male		RG58 (PVC) RG59 (Plenum) 20-22 AWG	50Ω	.116" - .146"	.195" - .242"	Nickel (body) Gold (contact)	10-pk 0E-BNC59PTOT
		RG59 (PVC) RG6 (Plenum) 18-22 AWG	50Ω	.146" - .185"	.242" - .275"	Nickel (body) Gold (contact)	10-pk 0E-BNCT56PTP
		RG59 (PVC) RG6 (Plenum) 18-22 AWG	75Ω	.146" - .185"	.242" - .275"	Nickel (body) Gold (contact)	10-pk 0E-BNCT5675T
Compression Plug Male		RG59 (PVC) 18-22 AWG	50Ω	.146"	.242"	Nickel (body) Gold (contact)	10-pk 0E-BNCCOMPTP
		RG59, RG6 (PVC)	75Ω	.146" - .185"	.242" - .275"	Nickel (body) Gold (contact)	10-pk 0E-BNCCOM75T
		RG59 (PVC) 20 AWG	75Ω	.146"	.242"	Nickel (body) Gold (contact)	10-pk 0E-BNCCOMH75
							100 (jar) 0E-BNCCMH75C
Crimp Plug Male		RG59, RG6 (PVC)	50Ω	.146" - .185"	.242" - .275"	Nickel (body) Gold (contact)	10-pk 0E-BNC2UTP
		RG58 (PVC) RG59, RG6 (PVC or Plenum)	50Ω	.116" - .146" - .185"	.195" - .242" - .275"	Nickel (body) Gold (contact)	10-pk 0E-BNCCRIMPT
							100 (jar) 0E-BNCCRIMPC
		RG58 (PVC) RG59, RG6 (PVC or Plenum)	75Ω	.116" - 0.146" - .185"	.195" - .242" - 0.275"	Nickel (body) Gold (contact)	10-pk 0E-BNCCR75TP
							100 (jar) 0E-BNCCRI75C
							10-pk 0E-BNCU75TP
T-Connector Male/2x Female		--	50Ω	--	--	Nickel (body) Gold (contact)	10-pk 0E-BNCM22FTP
Coupler Female/Female		--	50Ω	--	--	Nickel (body) Gold (contact)	10-pk 0E-BNCFFTP
		--	75Ω	--	--	Nickel (body) Gold (contact)	10-pk 0E-BNCFF75TP
Adapter BNC Plug/F Jack		--	75Ω	--	--	Nickel (body) Gold (contact)	10-pk 0E-BNCM22F75
Adapter BNC Jack/RCA Plug		--	50Ω	--	--	Nickel (body) Gold (contact)	10-pk 0E-BNCFRCAMT

For more information, contact
your ADI salesperson or visit
adiglobal.com/adiexclusivebrands

ADI
PRO