

FLEXUS SUB 200

COMPACT WIRELESS 12" SUBWOOFER



BIG BASS, SMALL FOOTPRINT

The Flexus 12" subwoofer packs a lot of punch per square inch thanks to careful Klipsch engineering. Enjoy powerful bass with plenty of depth and musicality - without latency.

BETTER TOGETHER

Two subs are better than one. As your tastes and square footage grow, so do the demands you'll have for deep, powerful bass. By having two identical Flexus 12" Subwoofers, you'll smooth out the peaks and nulls typically experienced by a single subwoofer arrangement.

QUICK, CONVENIENT CONNECTION

Klipsch transport technology built into every Flexus product means your whole home entertainment ecosystem functions fast and efficiently. Setup is simple, latency is low and booming bass is only a cord away.

SIMPLE SETUP, SLEEK STYLE

Style matters. That's why Klipsch Flexus was meticulously engineered down to the last millimeter with premium materials, thoughtful design, and calculated engineering for a family of products to fit any space or aesthetic.

ECO-CONSCIOUS PACKAGING

We're committed to providing great sound for generations - which is why our packaging is designed to be earth-friendly, with careful consideration to minimize waste and maximize recyclability.

Powered by **ONKYO**

Meticulously reviewed by our engineers at sister company Onkyo, the Klipsch Flexus system passed over 1,000 rigorous tests to ensure awesome audio performance and stellar interconnectivity.

SPECIFICATIONS	
FREQUENCY RESPONSE	26Hz - 250Hz +/- 3dB
MAX ACOUSTIC OUTPUT	103.7dB
AMPLIFIER TYPE	Class D
WOOFER	12" Long Throw Paper Cone Woofer
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Sealed
INPUTS	RCA/LFE Line In • Flexus Transport 2.4Ghz Wireless
HEIGHT	15.25" (387mm)
WIDTH	15.25" (387mm)
DEPTH	15.25" (387mm)
WEIGHT	36lbs(16.3kgs)
INCLUDED ACCESSORIES	(1) 2.0m Right-Angle IEC Power Cord (Region Specific) (1) Flexus Transport Wireless dongle (1) User Manual
USB INPUT	(1) USB Type-A Connection For System Updates and playback of MP3 files.

MODEL NAME	SKU	REGION	UPC	EAN
FLEXUS SUB 200	1072086	NA	743878066722	743878066722
FLEXUS SUB 200	1072088	EUA	743878066739	743878066739
FLEXUS SUB 200	1072089	CCC	743878066746	743878066746