



Summary




Combining advanced surveillance features with active deterrence, the Luma 720 Series POE Floodlight Camera delivers enhanced safety, reliability, and performance. With Power over Ethernet (PoE) connectivity, this model is ideal for professional installs where consistent power and network stability are critical.

Unlike traditional single-lens cameras, the 720 Series features a dual-lens design that delivers a wider field of view and higher-resolution imaging across a broader area — perfect for full coverage of driveways, yards, or large outdoor zones.

Integrated floodlight illumination and hybrid night vision give you full control over nighttime footage. Choose traditional IR for wide-area black-and-white visibility, or switch to full-color mode using powerful built-in floodlights that highlight important details like faces, vehicles, and clothing.

Dimensions

Unit: mm



Accessory Compatibility

LUM-A20-JB-VF-BTB

LUM-A20-JB-VF-BTW

Specifications

| Specifications | LUM-720-IP-FLDW | LUM-720-IP-FLDB |
|------------------------|--|--|
| Color | White | Black |
| Image Sensor | 7MP (Dual 4MP 1/18") CMOS | 7MP (Dual 4MP 1/18") CMOS |
| Maximum Resolution | 4560×1520 | 4560×1520 |
| Frame Rate | 30fps | 30fps |
| Shutter Speed | 1 - 1/16000 sec | 1 - 1/16000 sec |
| Minimum Illumination | 0.001 Lux @ F1.6, AGC ON 0 Lux with IR 0 Lux with LED | 0.001 Lux @ F1.6, AGC ON 0 Lux with IR 0 Lux with LED |
| Aperture | F1.0 | F1.0 |
| Field of View | Horizontal: 200° Vertical: 60° | Horizontal: 200° Vertical: 60° |
| Focus | Fixed | Fixed |
| IR Range | 30m (98ft) | 30m (98ft) |
| White LED Range | 15m (50ft) | 15m (50ft) |
| WDR | >100dB | >100dB |
| Backlight Compensation | Yes | Yes |
| Highlight Compensation | Yes | Yes |
| DNR | 2D/3D DNR | 2D/3D DNR |
| S/N Ratio | >42dB* | >42dB* |
| Smart Alarm | Motion detection, sensor alarm, SD card error, SD card full, IP address conflict, audio alarm, light alarm | Motion detection, sensor alarm, SD card error, SD card full, IP address conflict, audio alarm, light alarm |

| Specifications | LUM-720-IP-FLDW | LUM-720-IP-FLDB |
|-------------------------------|---|---|
| Recording Trigger | Motion, Line Crossing, Intrusion, Scene Change, Video Blur | Motion, Line Crossing, Intrusion, Scene Change, Video Blur |
| AI Event | Human, Vehicle & Non-motor Vehicle Detection | Human, Vehicle & Non-motor Vehicle Detection |
| Motion Detection | Yes | Yes |
| Image Snapshot | Yes | Yes |
| Streams | Main stream: H.265 / H.264 Sub/Third/Fourth stream: H.265 / H.264 / MJPEG | Main stream: H.265 / H.264 Sub/Third/Fourth stream: H.265 / H.264 / MJPEG |
| Main Stream | 4560x1520 | 4560x1520 |
| Sub Stream | 704x480 | 704x480 |
| Third Stream | 704x480 | 704x480 |
| Fourth Stream | 1920x1080 | 1920x1080 |
| Supported Resolutions | 4560x1520, 2688x1520, 1920x1080, 1280x720, 704x480 | 4560x1520, 2688x1520, 1920x1080, 1280x720, 704x480 |
| Bit Rate | 512kbps - 8Mbps (VBR/CBR) | 512kbps - 8Mbps (VBR/CBR) |
| Audio Compression | G.711 a/ulaw | G.711 a/ulaw |
| Microphone | 1CH built-in microphone | 1CH built-in microphone |
| SD Card Support | Built-in micro SD card slot; up to 1TB | Built-in micro SD card slot; up to 1TB |
| Speaker | 1CH built-in Speaker (82dB, level measured at 15ft distance) | 1CH built-in Speaker (82dB, level measured at 15ft distance) |
| Audio Input/Output Connectors | No | No |
| Alarm Contact Inputs/Outputs | No | No |
| CVBS Output | No | No |
| Reset Button | Yes | Yes |
| Network / Ethernet Desc. | Yes | Yes |
| Power over Ethernet | IEEE 802.3bt | IEEE 802.3bt |
| Network Protocol | IPV4, IPV6, HTTP, HTTPS, 802.1x, FTP, SMTP, DNS, DDNS, UPnP, SNMP, NTP, P2P, RTSP, RTP, RTCP, TCP/IP, UDP, IGMP, ICMP, DHCP | IPV4, IPV6, HTTP, HTTPS, 802.1x, FTP, SMTP, DNS, DDNS, UPnP, SNMP, NTP, P2P, RTSP, RTP, RTCP, TCP/IP, UDP, IGMP, ICMP, DHCP |
| Interface Protocol | ONVIF | ONVIF |
| Browser Support | Chrome, Firefox, Safari, Edge | Chrome, Firefox, Safari, Edge |
| Power Consumption | 37.8W @ 54V | 37.8W @ 54V |
| Outdoor Rating | IP66 | IP66 |
| Defog | No | No |
| Certifications | ETL Listed, CE, FCC, UKCA, NDAA Compliant, ONVIF Conformance | ETL Listed, CE, FCC, UKCA, NDAA Compliant, ONVIF Conformance |
| Operating Temperature | -4°F - 122°F (-20°C - 50°C) | -4°F - 122°F (-20°C - 50°C) |
| Operating Humidity | Less than 95% non-condensing | Less than 95% non-condensing |
| Storage Temperature | -22°F - 140°F (-30°C - 60°C) | -22°F - 140°F (-30°C - 60°C) |
| Dimensions (W x H x D) | 10.74 x 8.48 x 7.51in (273 x 215.6 x 191mm) | 10.74 x 8.48 x 7.51in (273 x 215.6 x 191mm) |
| Weight | 2.66 lbs (1.21 kg) | 2.66 lbs (1.21 kg) |