

VERANDA 4
FULL-SHADE
OUTDOOR TV



SUNBRITE VERANDA 4

FULL-SHADE OUTDOOR
SMART TV

The Veranda 4 delivers 600 nits of 4K60 HDR10 brightness for full-shade outdoor viewing and a vibrant, energy-efficient display. Easy to install, it includes Wi-Fi, Bluetooth (BT5.0), voice control, direct & discreet IR, and IP control for easy integration and seamless performance.

SunBriteTV.com



A Refined Way to Enjoy the Shade

Deliver premium full shade performance with RGB-W technology on a direct LED backlight screen for brighter pictures and up to 2-4x the brightness of many indoor TVs. The anti-glare screen with Quarter Wave Plate Polarizer (QWP) improves visibility, even if viewers are wearing sunglasses.

IP55

Entertainment Built to Last

With a high operating temperature range, conformal coating on internal components that protect against humidity, and an IP55 rating, this TV can withstand the hottest summer days and almost any storm.

webOS

Streaming Made Easy

Content selection and customization is simple with webOS smart functionality, as well as through the ability to connect almost any streaming device of their choice.



	SB-V4-49-BL	SB-V4-55-BL	SB-V4-65-BL	SB-V4-75-BL
Backlight Compensation	600 nits (cd/m2)	600 nits (cd/m2)	600 nits (cd/m2)	600 nits (cd/m2)
Weatherproof Rating	IP55	IP55	IP55	IP55
VESA Mounting Positions	200×200	400×400	400×400	400×400
Housing	Powder-coated aluminum	Powder-coated aluminum	Powder-coated aluminum	Powder-coated aluminum
Power	GFCI protected 100-240 VAC, 50/60Hz, 4.7A max	GFCI protected 100-240 VAC, 50/60Hz, 4.7A max	GFCI protected 100-240 VAC, 50/60Hz, 4.7A max	GFCI protected 100-240 VAC, 50/60Hz, 4.7A max
HDMI Connectors	3 inputs (Supports HDMI 2.1, HDMI 2.0, HDM11.4, HDCP 1.4a HDCP 2.2) (eARC on HDMI 2)	3 inputs (Supports HDMI 2.1, HDMI 2.0, HDM11.4, HDCP 1.4a HDCP 2.2) (eARC on HDMI 2)	3 inputs (Supports HDMI 2.1, HDMI 2.0, HDM11.4, HDCP 1.4a HDCP 2.2) (eARC on HDMI 2)	3 inputs (Supports HDMI 2.1, HDMI 2.0, HDM11.4, HDCP 1.4a HDCP 2.2) (eARC on HDMI 2)
Smart TV	webOS	webOS	webOS	webOS
Video Inputs	Composite Video xl, L/R Audio Inputs xl	Composite Video xl, L/R Audio Inputs xl	Composite Video xl, L/R Audio Inputs xl	Composite Video xl, L/R Audio Inputs xl
Screen Resolution	3840x2160	3840x2160	3840x2160	3840x2160
Back Light	Direct LED	Direct LED	Direct LED	Direct LED
Screen Description	Anti-Glare with Quarter Wave Plate Polarization (QWP) screen RGB-W Tech	Anti-Glare with Quarter Wave Plate Polarization (QWP) screen RGB-W Tech	Anti-Glare with Quarter Wave Plate Polarization (QWP) screen RGB-W Tech	Anti-Glare with Quarter Wave Plate Polarization (QWP) screen RGB-W Tech
Contrast Ratio	1100:1	1100:1	1100:1	1100:1
Frame Rate	60 Hz	60 Hz	60 Hz	60 Hz
Viewing Angle	R/L 178°, U/D 178°	R/L 178°, U/D 178°	R/L 178°, U/D 178°	R/L 178°, U/D 178°
Response Time	8 milliseconds	8 milliseconds	8 milliseconds	8 milliseconds
TV Formats	2160p (HDMI only), 1080p, 1080i, 720p, 720i, 480p, 480i	2160p (HDMI only), 1080p, 1080i, 720p, 720i, 480p, 480i	2160p (HDMI only), 1080p, 1080i, 720p, 720i, 480p, 480i	2160p (HDMI only), 1080p, 1080i, 720p, 720i, 480p, 480i
Control Set	Direct & Discreet IR control, IP control	Direct & Discreet IR control, IP control	Direct & Discreet IR control, IP control	Direct & Discreet IR control, IP control
Included Speaker	2 x 8W down firing internal speakers	2 x 8W down firing internal speakers	2 x 8W down firing internal speakers	2 x 8W down firing internal speakers
Operating Temperature	32° to 122° F. (0° to 50° C)	32° to 122° F. (0° to 50° C)	32° to 122° F. (0° to 50° C)	32° to 122° F. (0° to 50° C)
Non-Operating Temperature	-24° to 140° F. (-31° to 60° C)	-24° to 140° F. (-31° to 60° C)	-24° to 140° F. (-31° to 60° C)	-24° to 140° F. (-31° to 60° C)
Dimensions	44 x 26 x 4.25 in. (1118 x 660 x 108 mm)	49.28 x 28.8 x 4.24 in. (1251.6 x 731.5 x 107.7 mm)	57.9 x 33.6 x 4.2 (1470.4 x 854.5 x 107.4mm)	66.62 x 38.54 x 4.23 in. (1692.1 x 978.9 x 107.4 mm)
Weight	37.0 lb. / 17.0 kg	46.5 lb. / 21.1 kg	59.0 lb. / 26.8 kg	82.9 lb. / 37.6 kg