

SIGNATURE 2 SERIES
PARTIAL SUN
OUTDOOR TV



OUTDOORS JUST GOT BETTER

The Signature Series is designed for partial-sun outdoor areas like patios, decks, and anywhere else high-ambient light exists. Unlike an indoor TV, the Signature offers a fully weatherproof design and a stunning picture specifically designed for outdoor viewing.

CREATE AN OUTDOOR
EXPERIENCE TODAY

SunBriteTV.com



Safe for Outdoor Use

Made for permanent outdoor installation, the Signature Series features a rust-proof aluminum frame and weatherproof media bay for year-round entertaining with total peace of mind.



Ultra-Bright Picture

With TruVision™ anti-glare technology and 700 NITS of 4K HDR clarity, you get a brilliant display on the brightest days. Indoor TVs only provide 100-300 NITS, which makes clear outdoor viewing impossible.



Always the Perfect Fit

The Signature Series features a thin profile in four sizes starting at 45" and going up to 75". With a powder-coated finish that comes in three colors, it fits seamlessly into any environment.



SUNBRITE

05052022 TS



Model Dimensions Comparison

	SB-S2-75-4K	SB-S2-65-4K	SB-S2-55-4K
Size	75"	65"	55"
Color Options	Black	Black	Black
Audio Output Connectors	Digital SPDIF Audio (Fixed)	Digital SPDIF Audio (Fixed)	Digital SPDIF Audio (Fixed)
Inputs	HDMI Input x2 (HDMI 2.0, HDMI 1.4, HDCP 2.2) 3840x2160 @ 60Hz, Binary 540 Series 4K Ultra HD HDBaseT Long-Range Transmitter with IR, RF Antenna/CATV (ATSC/QAM/NTSC) x1, YPbPr plus Stereo Audio x2, Composite Video x1, L/R Audio Inputs x1, VGA DB15hd	HDMI Input x2 (HDMI 2.0, HDMI 1.4, HDCP 2.2) 3840x2160 @ 60Hz, B-540-TX-330-IR, RF Antenna/CATV (ATSC/QAM/NTSC) x1, YPbPr plus Stereo Audio x2, Composite Video x1, L/R Audio Inputs x1, VGA DB15hd (up to 1920x1080) x1	HDMI Input x2 (HDMI 2.0, HDMI 1.4, HDCP 2.2) 3840x2160 @ 60Hz, B-540-TX-330-IR, RF Antenna/CATV (ATSC/QAM/NTSC) x1, YPbPr plus Stereo Audio x2, Composite Video x1, L/R Audio Inputs x1, VGA DB15hd (up to 1920x1080) x1
Operating Temperature	-24-122°F	-24-122°F	-24-122°F
Power Consumption	100-240 VAC, 50-60 Hz 2.8 A Max (270 Watts/2.3a@120v)	100-240 VAC, 50-60 Hz 2.8 A Max (270 Watts/2.3a@120v)	100-240 VAC, 50-60 Hz 2.8 A Max (245 Watts/2.1a@120v)
Backlight	700 NITS (cd/m2)	700 NITS (cd/m2)	700 NITS (cd/m2)
Aspect Ratio	16:09	16:09	16:09
Screen Resolution	3840 x 2160 UHD 4K HDR	3840 x 2160 UHD 4K HDR	3840 x 2160 UHD 4K HDR
Contrast Ratio	4000:1	4000:1	4000:1
Frame Rate	60Hz	60Hz	60Hz
Viewing Angle	178° x 178°	178° x 178°	178° x 178°
Control Set	IP Control, RS232, Discrete IR, Concealed Rear IR Window	IP Control, RS232, Discrete IR, Concealed Rear IR Window	IP Control, RS232, Discrete IR, Concealed Rear IR Window
Included Speaker	None	None	None
Non-Operating Temperature	-24°-140°F	-24°-140°F	-24°-140°F
Dimensions (W x H x D)	TBD	58.03" x 33.63" x 3.57"	49.38" x 28.72" x 3.66"
Weight	95 lbs	66 lbs	65 lbs