GARDEN ARRAY

GA4 SATELLITE, GA10 SUBWOOFER





GARDEN ARRAY

GA4 SATELLITE, GA10 SUBWOOFER

The Triad Garden Array is a family of premium, all-weather landscape speakers that are the perfect combination of elegance, sound, and durability. This family includes the unique GA4 Satellite speakers and powerful GA10 Subwoofer, which are designed to be placed throughout flowerbeds or around the yard to blanket outdoor spaces with rich, beautiful audio. Triad Garden Array speakers are completely scalable for every outdoor listening experience, from courtyards and patios to entire residential estates.

The Triad GA4 Satellite speaker is built around a unique, Ultra-Broad Dispersion (UBD) driver that provides superior sound coverage using fewer speakers. GA4 Sats deliver a 150-degree listening area that is over 50% wider than traditional landscape speakers, allowing for broader speaker placement without compromising sound quality.

The GA10 Subwoofer is designed for both above- and below-ground installations, so the bass can be located exactly where you want it—on the patio or deck, or buried near a pool, gazebo, or pergola. Kits are available for either type of installation.

FEATURES

- · Compact size, designer friendly
- · Built for all weather conditions

GA4 SATELLITE

- IP65 all-weather enclosure and design
- Custom UBD™ (Ultra Broad Dispersion) driver provides consistent 150-degree-wide dispersion and total coverage without beaming or hot spotting
- The 4.5" UBD™ driver allows you to locate sats 10 15' (3 4.5 m) apart
- Compatible with 8 ohm or 70/100V systems
- Wall mounts sold separately; ground stakes included (adjustable mounting poles up to 18")

GA10 SUBWOOFER

- IP57 all-weather enclosure and design
- Requires Triad RackAmp 300
- 10" long-throw, weather-resistant, composite woofer
- Mount above or below ground with Garden Array Foot or Underground kits (sold separately)
- Maximum power handling 300 watts



GARDEN ARRAY GA4 SATELLITE, GA10 SUBWOOFER

GA4 SAT

GA4 SAT

SPECIFICATIONS

MATERIALS

(1) 4 1/2" (11.4 cm) nominal

Ultra Broad Dispersion Driver (UBD™) size Ultra Broad Dispersion Driver (UBD™) type

Custom hex-core diaphragm

GA10 SUB

(1) 10" (25.4 cm) nominal Composite

PERFORMANCE

Transformer taps

Impedance

8 ohm or 70/100V

87 dB

100 Hz - 20 kHz

70V: 3.75W, 7.5W, 15W, 30W

100V: 7.5W, 15W, 30W

15 - 60W direct, 3.75 - 35W per sat, @ 70/100V

10 - 15 ft (3 - 4.5 m) between sats

-58°F to +194°F (-50°C to +90°C)

GA10 SUB

4 ohm

Max output 102 dB 27 Hz - 300 Hz



300W

IP57

-58°F to +194°F (-50°C to +90°C)

Recommended amplifier power

Sensitivity (dB @ 2.83V, 1 m)

Frequency response (+/- 3 dB)

Recommended spacing

Weather-resistance

Enclosure ($\emptyset \times D$)

 $(max, min H \times \emptyset)$

Product weight

Shipping weight

Adjustable pole height

Operating temperature

DIMENSIONS GA4 SAT

 \emptyset 5 $\frac{1}{4} \times 7 \frac{7}{8}$ " (\emptyset 13.4 × 20 cm)

26 $\frac{3}{4}$ (max) - 11 $\frac{3}{4}$ (min) × Ø 1 $\frac{1}{16}$ " (67.9 (max) - 29.8 (min) × Ø 2.7 cm)

3.4 lb (1.5 kg) (pair)

8.3 lb (3.8 kg) (pair)

GA10 SUB

23.6 lb (10.72 kg) (each) 29 lb (13.15 kg) (each)

PRODUCT NUMBERS

Standard finish

GA4 SAT (pair)

30340-1

GA10 SUB (each)

30341-1

GA4 SAT WALL MOUNT KIT (2 MOUNTS)

Mount base (H × W)

GA10 SUB FOOT KIT

Mount with GA4 Sat attached (H)

Product number - 30352-1

 $3^{7/8} \times 2^{3/8}$ " (9.8 × 6.1 cm)

 $11^{1/4}$ " (28.6 cm)


Product number - 30351-1

Feet (quantity, 4) (H × W × D) $1^{1/8} \times 3^{3/4} \times 3^{3/4}''$ (2.8 × 9.5 × 9.5 cm)

Wall Mount Kit (GA10 Sub)



Foot Kit (GA10 Sub)



(GA10 Sub)

13 ¹³/₁₆"

[35 cm]

GA10 SUB UNDERGROUND KIT

Height (from woofer base to top of cap)

Cap $(\emptyset \times H)$

Pipe

Product number - 30350-1

28 1/2" (72.4 cm)

 \emptyset 10 $\frac{1}{4} \times \frac{3}{4} = \frac{1}{2}$ " (\emptyset 26 × 8.9 cm)

Ø 4 ⁵/₁₆" (Ø 10.9 cm)

DIMENSIONS

GA4 SAT



Wall mount



