SILVER SURROUND

ON-WALL, IN-WALL





SILVER SURROUND

ON-WALL, IN-WALL

Fill your theater or media room with vivid, life-like sound—captivating audiences with Triad Silver Surround speakers. Designed to work with high-powered AVRs, these bipole speakers offer full-frequency sound reproduction, delivering powerful output for optimal, dynamic audio. Carefully chosen drivers and components work well with all surround sound formats, meeting the demands of every home cinema.

In an industry of generic, mass-produced products, Triad combines craftsmanship and customization in every order. Handcrafted in the US using the finest materials and components, Triad's fully engineered, sealed, and internally braced MDF enclosures deliver intricate acoustics and effortless playback, actualizing the artist's intent.

Triad's Silver Surrounds offer a professional-grade cinematic experience, achieving unobtrusive elegance while retaining the integrity of sound. Complete the full home theater experience by pairing the Silver Surround with Triad LCRs, satellites, and subs.

FEATURES

- · Compact, bipole design
- · AcoustiPerf metal grill
- Fully engineered, premium MDF enclosure
- Acoustic suspension
- · Custom paint matching available

ON-WALL

The On-Wall Silver Surround can be used in arrays of multiple pairs in larger rooms and can be either wall mounted or ceiling mounted to suit the situation.

IN-WALL

With its compact dimensions and ultra-low-profile installed appearance, the In-Wall Silver Surround can be mounted in walls or the ceiling, regardless of the direction the ceiling joists run.



SILVER SURROUND ON-WALL, IN-WALL

SPECIFICATIONS

MATERIALS ON-WALL

Tweeter size (2) 4" (10 cm) Tweeter type Broad dispersion polycone

(1) $6^{1/2}$ " (17 cm) Woofer size Paper/fiber blend Woofer type

IN-WALL/4

(2) 4" (10 cm)

Broad dispersion polycone

(1) $6^{1/2}$ " (17 cm)

Paper/fiber blend

PERFORMANCE

Recommended amplifier power Impedance Sensitivity (dB @ 2.83V, 1 m) Peak output (measured, 1 m)

Frequency response (+/- 3 dB)

ON-WALL

50 - 150W 6 ohm 85 dB 106 dB

80 Hz - 20 kHz

IN-WALL/4

50 - 160W 6 ohm 86 dB 106 dB

80 Hz - 20 kHz



DIMENSIONS

Cabinet specifications $(L \times W \times D)$

> Hole cut out $(L \times W)$

Frameless grill dimensions $(L \times W)$

> NCB size Product weight (each)

Shipping weight (each)

ON-WALL

 $14^{15}/_{16} \times 14^{3}/_{16} \times 4^{3}/_{8}$ " (with grill) $(38 \times 36.1 \times 11.2 \text{ cm})$

15 lb (6.8 kg) 6.5 lb (7.5 kg)

IN-WALL/4

 $13 \frac{1}{2} \times 13 \frac{1}{2} \times 3 \frac{15}{16}$ " $(34.3 \times 34.3 \times 9.9 \text{ cm})$

13 5/8 × 13 5/8" $(34.6 \times 34.6 \text{ cm})$

 $14^{13}/_{16} \times 14^{13}/_{16}$ " $(37.6 \times 37.6 \text{ cm})$

13 lb (5.9 kg) 16 lb (7.3 kg)

PRODUCT NUMBERS

Silver Surround

Custom

ON-WALL


35008-1000-1 35008-1000-1-C


IN-WALL/4


45408-1000-1 45408-1000-1-C

DIMENSIONS

ON-WALL







IN-WALL/4

