



DETAIL LEGEND:

- ① FX LUMINAIRE "C-LL" LEDGE LIGHT FIXTURE PER PLAN.
- ② INSTALL MOUNTING PLATE TO WALL OR SURFACE PRIOR TO LAYING CAPSTONE (OPTIONAL)
- ③ FASTEN HOUSING ONTO MOUNTING PLATE OR DIRECTLY TO DESIRED SURFACE (OPTIONAL)
- ④ ADJACENT WALL OR SURFACE
- ⑤ DIRECT BURY, UF/UL, COPPER, LOW VOLTAGE CABLE WITH UL 486D (IEC/EN 60998) RATED WATERPROOF CONNECTION. LEAVE MINIMUM WIRE LOOP COILED BEHIND FIXTURE FOR FUTURE SERVICE.

NOTES

- A. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
- B. ACCEPTS 10-15 VOLTS - AC/DC.
- C. SEE PLAN LEGEND FOR LED BOARD OPTION, BEAM SPREADS, AND ACCESSORIES.
- D. ALWAYS REFER TO FX PRODUCT INSTALLATION NOTES PRIOR TO INSTALLATION.



C-LL, LEDGE LIGHT

FXLuminaire. U.C-LL.01

NOT TO SCALE

REV: 2020-02-14