


## SRP RGBW Strip Light **STANDARD PREMIUM**




---

PROJECT

---

CATALOG #

---


TYPE

---

NOTES

---

The vibrant and versatile SRP RGBW Strip Light makes it easier than ever to illuminate stair ledges, outdoor patios, hardscape elements, and more.



### Quick Facts

- Total RGBW control; SRP-CC Strip Light Color Controller required
- Standalone Mode can be used with our EX, PX, and DX models as well as any standard low-voltage transformer, allowing users to manually set Hue, Saturation, and values
- IP65 rating for top performance in tough outdoor conditions
- Each unit comes in 10' (3.1 m) lengths with 2" (51 mm) cutmarks for precision customization
- Two convenient control options: Standalone or Luxor Mode
- Luxor Mode allows a Luxor Controller to assign a Group and set Hue, Saturation, and Intensity values
- Extruded silicone body reduces hot spots, produces soft light distribution, and protects against harsh environments
- Comes with all necessary accessories, including solder- and adhesive-free splice connections that require no heat shrink, for seamless installation in any setting

# SRP RGBW Strip Light SPECIFICATIONS

Output	SRP RGBW
Total Lumens	24.25 lm/ft
Input Voltage	10 to 15 V
Input Power	1.7 W/ft
VA	2.9 VA/ft
Efficacy (lm/W)	18.6
Color Rendering Index (CRI)	52
Center Beam Candlepower	--
Dimming	Yes; must use SRP-CC Color Controller
Primary Dimming (Transformer)	--
Secondary Dimming (Fixture)	--
RGBW Available	Yes; Must be used with SRP-CC Color Controller
Minimum Rated Life L90 B10 (Hrs)	50,000
* For optimal performance, use a trailing-edge (reverse phase-cut) dimmer.	

# SRP RGBW Strip Light SPECIFICATIONS

## FX Luminaire

FX Luminaire is an industry-leading manufacturer of landscape and architectural lighting products with a focus on the advancement of LED technology and digital lighting control with zoning, dimming, and color adjustment capabilities. We offer a full spectrum of specification-driven lighting fixtures that can be utilized to create elegant, cutting-edge landscape lighting systems for commercial or residential applications. Our products are available exclusively via our extensive professional distributor network.

## Materials

Silicone

## Lamp

Integrated

## Finish

White

## Hardware

Includes 3" (76 mm) and 6" (152 mm) jumpers, splice clamps, LED spacer, end connector, and mounting clips.

## Wiring

20 AWG (0.8 mm); VW-1; 176°F (80°C); 300 V; 10' (3 m) length, prestripped

## Power

Input 10 to 15 VAC/VDC, 50/60 Hz. Remote transformer required (specify separately). SRP-CC Color Controller is also required to power the SRP RGBW Strip Light.

## Housing

Silicone

## Weight

10' (3.1 m) = 2.3 lbs (1.04 kg)

## Ambient Operating Temperature

0°F to 140°F (-18°C to 60°C)

## Sustainability

Innovation meets conservation in the design and manufacturing of our products. Where we can, we use recycled materials while maintaining superior functionality. Our LED products provide high-quality light at optimal energy efficiency, lifespan, and durability.

## Control

Compatible with the Luxor Controller, DX Controller, EX Transformer, and PX Transformer from FX Luminaire when installed with the SRP-CC Color Controller.

## Warranty

5-year limited warranty

## Listings



# SRP RGBW Strip Light ORDERING INFORMATION

Fixture	Length	Color	Finish
SRP	10 10 ft (3.1 m)	RGBW * Color	
	20 20 ft (6.1 m)		



EXAMPLE FIXTURE CONFIGURATION: SRP-XX-XXXX-XX



# SRP RGBW Strip Light PHOTOMETRICS

SRP RGBW Strip Light - Illuminance at a Distance

Distance	Center Beam fc	Beam Width	
Feet (Meters)	Foot-Candles (Lux)	Vertical: 115.7 °	Horizontal: 115.5 °
10.0' (3.1 m)	2.9 fc (1.1 lx)	10.5' (3.2 m)	10.5' (3.2 m)
20.0' (6.1 m)	0.7 fc (0.3 lx)	21.3' (6.5 m)	21.2' (6.5 m)
3.3' (1.0 m)	0.3 fc (0.1 lx)	31.8' (9.7 m)	31.7' (9.7 m)
6.7' (2.0 m)	0.2 fc (0.1 lx)	42.3' (12.9 m)	42.2' (12.9 m)
13.3' (4.1 m)	0.1 fc (0 lx)	53.1' (16.2 m)	52.9' (16.1 m)
16.7' (5.1 m)	0.1 fc (0 lx)	63.6' (19.4 m)	63.6' (19.3 m)


# SRP RGBW Strip Light ORDERING INFORMATION

MOUNTING OPTIONS: Specify Separately

Mounts	Catalog No.		Mounts	Catalog No.	
Channel Mount, SRP - 3.3 ft. (1 m), Qty: 3	SRP-CHN		Hardscape Mount, SRP	SRP-MNT	



# SRP RGBW Strip Light ORDERING INFORMATION

POWER OPTIONS: Specify Separately

Power	Catalog No.		Power	Catalog No.
SRP-CC Color Controller	SRP-CC			

# SRP RGBW Strip Light ORDERING INFORMATION

SPLICING OPTIONS: Specify Separately

Splicing	Catalog No.		Splicing	Catalog No.	
<b>Splice Connectors, SRP- RGBW</b>	SRP-CONNECT- RGBW		<b>Cutter Tool, SRP RGBW</b>	SRP-CUT	
	SRP-RGBW-T	