

Product	Device Type	HDBaseT Transmission*	4K/UHD & HDR Capability	Signals Extended	Device Powering	Atlona Switcher Compatibility	Additional Features
AT-UHD-EX-70C-TX	Transmitter	230 feet (70 meters)	4K/60 4:2:0 4K/24 HDR10 130 feet (40 meters)	HDMI, RS-232, IR	Local powering	SW-5000ED and CLSO Series with HDBaseT inputs	Ideal for extending AV and control to an HDBaseT-equipped projector
AT-UHD-EX-70C-RX	Receiver	230 feet (70 meters)	4K/60 4:2:0 4K/24 HDR10 130 feet (40 meters)	HDMI, RS-232, IR	Remotely powered by AT-UHD-EX-70C-TX or Atlona switcher	UHD-PRO3, UHD-CAT, SW, CLSO, and HDVS-200 Series with HDBaseT outputs	
AT-HDR-EX-70C-KIT	Transmitter + Receiver Kit	230 feet (70 meters)	4K/60 4:4:4 4K/60 HDR10 Dolby Vision @ 30 Hz 130 feet (40 meters)	HDMI, RS-232, IR	Receiver powered by transmitter		
AT-UHD-EX-70C-KIT	Transmitter + Receiver Kit	230 feet (70 meters)	4K/60 4:2:0 4K/24 HDR10 130 feet (40 meters)	HDMI, RS-232, IR	Receiver powered by transmitter	SW-5000ED and CLSO Series with HDBaseT inputs and outputs	
AT-UHD-EX-70-KIT	Transmitter + Receiver Kit	230 feet (70 meters)	4K/60 4:2:0 4K/24 HDR10 130 feet (40 meters)	HDMI only	Receiver powered by transmitter	SW-5000ED and CLSO Series with HDBaseT inputs and outputs	
AT-HDR-EX-70-2PS	Transmitter + Receiver Kit	230 feet (70 meters)	4K/60 4:4:4 4K/60 HDR10 Dolby Vision @ 30 Hz 130 feet (40 meters)	HDMI only	Local powering at transmitter and receiver		
AT-UHD-EX-70-2PS	Transmitter + Receiver Kit	230 feet (70 meters)	4K/60 4:2:0 4K/24 HDR10 130 feet (40 meters)	HDMI only	Local powering at transmitter and receiver		
AT-UHD-EX-100CE-TX	Transmitter	330 feet (100 meters)	4K/60 4:2:0 4K/24 HDR10	HDMI, RS-232, IR, Ethernet	Local powering	SW-5000ED and CLSO Series with HDBaseT inputs	Ideal for extending AV and control to an HDBaseT-equipped projector
AT-UHD-EX-100CE-TX-PD	Transmitter	330 feet (100 meters)	4K/60 4:2:0 4K/24 HDR10	HDMI, RS-232, Ethernet	Remotely powered by AT-UHD-EX-100CE-RX-PSE or Atlona switcher	SW-5000ED and CLSO Series with HDBaseT inputs	
AT-UHD-EX-100CE-RX	Receiver	330 feet (100 meters)	4K/60 4:2:0 4K/24 HDR10	HDMI, RS-232, IR, Ethernet	Remotely powered by AT-UHD-EX-100CE-RX-PSE or Atlona switcher	UHD-PRO3, UHD-CAT, SW, CLSO, and HDVS-200 Series with HDBaseT outputs	
AT-UHD-EX-100CE-RX-PSE	Receiver	330 feet (100 meters)	4K/60 4:2:0 4K/24 HDR10	HDMI, RS-232, IR	Local powering	UHD-PRO3, UHD-CAT, SW, CLSO, and HDVS-200 Series with HDBaseT outputs	4K/UHD extension from HDVS-200 transmitters
AT-UHD-EX-100CE-KIT	Transmitter + Receiver Kit	330 feet (100 meters)	4K/60 4:2:0 4K/24 HDR10	HDMI, RS-232, IR, Ethernet	Receiver powered by transmitter	SW-5000ED and CLSO Series with HDBaseT inputs and outputs	
AT-HDR-EX-100CEA-KIT	Transmitter + Receiver Kit	330 feet (100 meters)	4K/60 4:4:4 4K/60 HDR10 Dolby Vision @ 30 Hz	HDMI, RS-232, IR, Ethernet	Receiver powered by transmitter		Provides audio return pathway
AT-UHD-EX-100CEA-KIT	Transmitter + Receiver Kit	330 feet (100 meters)	4K/60 4:2:0 4K/24 HDR10	HDMI, RS-232, IR, Ethernet	Receiver powered by transmitter		Provides audio return pathway

\* Information on this data sheet is subject to change. Refer to our website [www.atlona.com](http://www.atlona.com) for the most up to date specifications.