

Product	Device Type	HDBaseT Transmission*	Inputs	4K/UHD & HDR Capability	Signals Extended	Device Powering	Atlona Switcher Compatibility	Additional Features
AT-HDVS-150-TX	AV switcher + transmitter	230 feet (70 meters)	2 HDMI 1 VGA		AV Control (internal)	Remotely powered by AT-HDVS-150-RX		
AT-HDVS-150-TX-PSK	AV switcher + transmitter	230 feet (70 meters)	2 HDMI 1 VGA		AV Control (internal)	Remotely powered by AT-HDVS-150-RX		Ideal for extending AV to an HDBaseT-equipped projector
AT-HDVS-150-TX-WP	AV switcher + transmitter US two-gang wall plate	230 feet (70 meters)	1 HDMI 1 VGA		AV Control (internal)	Remotely powered by AT-HDVS-150-RX		
AT-HDVS-150-RX	Receiver + HD scaler	230 feet (70 meters)			AV Control (internal)	Local powering		
AT-HDVS-150-KIT	Transmitter + receiver kit AT-HDVS-150-TX AT-HDVS-150-RX	230 feet (70 meters)	2 HDMI 1 VGA		AV Control (internal)	Transmitter powered by receiver		
AT-HDVS-200-TX	Transmitter + Receiver Kit	330 feet (100 meters)	2 HDMI 1 VGA	4K/60 4:2:0 With AT-UHD-EX-100CE-RX-PSE or Atlona switcher	AV, RS-232, Ethernet	Remotely powered by AT-HDVS-200-RX, AT-UHD-EX-100CE-RX-PSE, or Atlona switcher	SW-5000ED and CLSO Series with HDBaseT inputs	
AT-HDVS-200-TX-PSK	Transmitter	330 feet (100 meters)	2 HDMI 1 VGA	4K/60 4:2:0 With AT-UHD-EX-100CE-RX-PSE or Atlona switcher	AV, RS-232, Ethernet	Remotely powered by AT-HDVS-200-RX, AT-UHD-EX-100CE-RX-PSE, or Atlona switcher	SW-5000ED and CLSO Series with HDBaseT inputs	Ideal for extending AV and control to an HDBaseT-equipped projector
AT-HDVS-200-TX-WP	Transmitter	330 feet (100 meters)	1 HDMI 1 VGA	4K/60 4:2:0 With AT-UHD-EX-100CE-RX-PSE or Atlona switcher	AV, RS-232, Ethernet	Remotely powered by AT-HDVS-200-RX, AT-UHD-EX-100CE-RX-PSE, or Atlona switcher	SW-5000ED and CLSO Series with HDBaseT inputs	
AT-HDVS-200-TX-WP-BLK	Receiver	330 feet (100 meters)	1 HDMI 1 VGA	4K/60 4:2:0 With AT-UHD-EX-100CE-RX-PSE or Atlona switcher	AV, RS-232, Ethernet	Remotely powered by AT-HDVS-200-RX, AT-UHD-EX-100CE-RX-PSE, or Atlona switcher	SW-5000ED and CLSO Series with HDBaseT inputs	Interchangeable black and white wall-plates
AT-HDVS-210H-TX-WP	Receiver	330 feet (100 meters)	2 HDMI	4K/60 4:2:0 With AT-UHD-EX-100CE-RX-PSE or Atlona switcher	AV, RS-232, Ethernet (via compatible RX)	Remotely powered by AT-HDVS-200-RX, AT-UHD-EX-100CE-RX-PSE, or Atlona switcher	SW-5000ED and CLSO Series with HDBaseT inputs	Interchangeable black and white wall-plates
AT-HDVS-210U-TX-WP	Transmitter + Receiver Kit	330 feet (100 meters)	1 HDMI 1 USB-C	4K/60 4:2:0 With AT-UHD-EX-100CE-RX-PSE or Atlona switcher	AV, RS-232, Ethernet (via compatible RX)	Remotely powered by AT-HDVS-200-RX, AT-UHD-EX-100CE-RX-PSE, or Atlona switcher	SW-5000ED and CLSO Series with HDBaseT inputs	Interchangeable black and white wall-plates
AT-HDVS-200-RX	Receiver	330 feet (100 meters)			AV, RS-232, Ethernet	Local powering	Omega, Opus, UHD-PRO3, UHD-CAT, SW, and CLSO Series with HDBaseT outputs	
AT-HDVS-SC-RX	Transmitter + Receiver Kit	330 feet (100 meters)	1 HDBaseT 1 HDMI	4K/30 4:4:4	AV, RS-232, Ethernet, USB	Local powering	Omega, Opus, UHD-PRO3, UHD-CAT, SW, and CLSO Series with HDBaseT outputs	
AT-UHD-HDVS-300-KIT	Transmitter + Receiver Kit	330 feet (100 meters)	3 HDMI (1 at RX) 1 VGA 1 DisplayPort	4K/60 4:2:0	AV, RS-232, Ethernet, USB	Transmitter powered by receiver		Ideal for integrating PCs, USB mics and speakerphones, and touch displays

* Information on this data sheet is subject to change. Refer to our website www.atlona.com for the most up to date specifications.