

Strong Projector Ceiling Mount

SM-PROJ2-L-BLK & SM-PROJ2-L-WH



Strong Mounts – Making Installations Easier and Safer

Snap One's™ revamped Strong Ceiling Projector Mount is manufactured with high-grade steel for improved durability and to support projectors up to 75 pounds. An updated quick-release feature makes future maintenance a breeze.

Adjustable Mounting Arms

To fit as many projectors as possible, the Strong Projector Ceiling Mount features adjustable arms.

Cable Management

Integrated cable management keeps cables and wires concealed and organized for a clean, finished look.

Detachable Mounting Plate

Faster installations and re-installations are possible, all without having to re-align the projector.

Perfect Image 360°

360-degree rotating joint allows for flexibility in angles and viewing ability.

Adjust to Optimal Image

Adjustable support arms with a 19-degree tilt and 8-degree swivel ensure your best-projected image.

Durable Strong Support

Manufactured using high-grade steel for durability and support up to 75 pounds.

Beyond Compatible

Using the standard 1.5-inch NPT pipe size, the SM-PROJ2-L (BL/WH) interface bracket is compatible with various extension poles and ceiling plates already available in Snap One's Strong portfolio.

Specifications

Maximum Load	75lbs (34kg)
Tilt	19°
Weight	5.3lbs
Roll	8°
Rotation	180°
Dimensions	140x470x470mm (5.5"x18.5"x18.5")



Strong Projector Ceiling Mount

Ceiling Plates (Including AntiVibration), I-Beam Mount, & Dual Joist Mount

The Carbon Series Ceiling System offers a wide range of attachment solutions to fit your installation, including square or circular ceiling plates for flat surfaces, I-beam mounts with .63 inches to 10.75 inches of compatibility, and dual joist ceiling mounts for wood joist mounting. These parts are universally compatible with 1.5-inch NPT threaded receivers.



Universal Fit Adjustable Extension Pole + Fixed Extension Pole for Ceiling Mounts 3"–60"

Designed to work best with the Strong Ceiling Mounts Series and universally compatible with 1.5-inch NPT threaded receivers.

