





The CLIQ.mini is a small but powerful entry-level smart home control hub intended for volume deployment. The CLIQ.mini lowers overall system cost, to both the dealer and the homeowner, while simplifying project configuration and slashing installation time.

- Easy to install and configure
- Simple "one-wire" installation
- Powered via PoE or micro USB power supply
- Wall mountable or tabletop
- Built-in Wi-Fi and 908.4 MHz transceiver
- Automatic software updates
- Device auto-discovery
- Remote Cloud-based management
- Homeowner configurable Scenes, schedules, and notifications



Technical Specifications	
CPU	
Processor	Quad core 900MHz
Memory	1 GB DDR2, 8GB flash
Operating System	Linux
I/O	
Network	1 Ethernet port, 8-wire RJ45 with LED indicators for diagnostic use; 10/100/1000 BaseT Ethernet port
Power	802.11af PoE or 5 VDC over micro USB
USB	2 USB 2.0 ports (for future functionality)
Connectivity	908.4 MHz transceiver
WiFi	802.11n
General	
Operating Temperature	41° to 113°F (5° to 45°C)
Relative humidity	10 to 90% (non-condensing)
Dimensions (W x H x D)	3.85 x 5.98 x 1.32 in (97.79 x 151.9 x 33.53 mm)

CLIQ.mini will support:

- Lighting
- Security integration
- Door locks / garage door
- Thermostats
- IP video surveillance
- Multi-room audio
- Video entertainment
- Sensors
- Pool/spa
- Fireplace
- And more!

The information contained in this document is preliminary and is subject to change at the sole discretion of Clare Controls. Clare Controls will have no liability for delay in the delivery or failure to deliver any of the products or features set forth in this document.

By making home technology simple, Clare provides exclusive benefits to integrators, builders, and homeowners. We offer innovative home automation solutions, Class D amplifiers, media distribution, controllable lighting, and IP CCTV components. For more information, visit clarecontrols.com.