



Clare Window/Door Sensor

CS-DWS-10



This Clare Window/Door Sensor is ideal for monitoring windows, doors, cabinets, drawers, and many other applications. Connect the Clare Window/Door Sensors to the Clare Security Panel with ease using wireless pairing.

- For sensing things that open or separate
- Magnet and internal reed switch operation
- 2 supplemental hardwire zones
- Cover tamper
- Strong, reliable RF signal
- 10-15 year battery life
- Low battery indication

Technical Specifications

General

Housing Dimensions	3.2 x 1.4 x 1" (8 x 3.5 x 2.5cm)
Weight (with battery)	1.9oz (53.8 grams)
Mounting Fastener	#4 or #6 screws (not provided)

Sensor Specifications

Frequency	433.92 MHz
Replacement Battery	One Panasonic CR123A
Nominal Battery Life	10 to 15 years
Battery Voltage	3.0 VDC (Nominal), 2.2 VDC (Low)
Current Draw	20 mA (Maximum), 0.6 uA (Quiescent)
Transmitted Indications	Cover tamper, low battery, supervision

Regulatory

Regulations	UL634, ULC634, ETL, FCC, IC
-------------	-----------------------------

Environmental

Operating Temperature	32° to 120°F (0° to 49°C)
Humidity	85% non-condensing relative humidity

By making home technology simple, Clare provides exclusive benefits to integrators, builders, and homeowners. We offer innovative home automation solutions, Class D amplifiers, media distribution, controllable lighting, and IP CCTV components. For more information, visit clarecontrols.com.