



## ClareOne Door/Window Sensor with External Contact

CLR-C1-DWCNT



The ClareOne Door/Window Sensor with external contact is a magnetic sensor device designed to fit seamlessly alongside a door frame or window sill. The sensor features terminals that allow connection for external input and transmits open (trip) or closed (restore).

### Specifications

Compatible panel	ClareOne (CLR-C1-PNL1)
Transmitter frequency	433MHz
Encrypted	Yes
Operating gap	0.38 in (9.65 mm)
Transmitted indications	Tamper and low battery
Supervisory keep-alive	60-70 minutes
Switch type	Open loop (external contact)
Battery type	(2x) CR2032
Battery life	10 years
Operating temperature	32 to 120°F (0 to 49°C)
Relative humidity	95% non-condensing
Sensor dimensions	2.75 x 1 x 0.5 in (70 x 25.5 x 12.7 mm)
Magnet dimensions	1.5 x 0.5 x 0.44 in (38.1 x 12.7 x 11.17 mm)
Water resistant	No
Certifications	FCC: 15.109 Class B 15.231, Industry Canada: ICES-003, RSS-210

- Superior RF performance, even on steel surfaces
- Dual tamper; cover and wall for added security
- Works on wood or steel door frames
- Effective with vertical or horizontal mount
- Pairs easily and quickly with the ClareOne panel

By making home technology simple, Clare provides exclusive benefits to integrators, builders, and homeowners. We offer innovative home automation solutions, wireless security, controllable lighting, and IP CCTV components. For more information, visit [clarecontrols.com](http://clarecontrols.com).