



ClareOne Door/Window Sensor with Shock Sensor

CLR-C1-DWSHK



The ClareOne Door/Window Sensor with shock sensor provides complete intrusion protection for windows. The sensor detects both a contact opening and window impact or breaking glass.

Specifications

Compatible panel	ClareOne (CLR-C1-PNL1)
Transmitter frequency	433MHz
Encrypted	Yes
Operating gap	0.38 in (9.65 mm)
Transmitted indications	Tamper and low battery
Supervisory keep-alive	60-70 minutes
Shock sensitivity adjust	Yes
Battery type	(2x) CR2032
Battery life	10 years
Operating temperature	32°F to 120°F (0°C to 49°C)
Relative humidity	95% non-condensing
Dimensions (W x H x D)	2.25 x 1.0 x 0.50 in (57.15 x 25.4 x 12.7 mm)
Water resistant	No
Certifications	FCC: 15.109 Class B 15.231, Industry Canada: ICES-003, RSS-210

- Superior RF performance on metal surfaces
- LED activates on impact activation
- Adjustable shock detection sensitivity
- Effective with vertical or horizontal mounting
- Detects vibrations and impact
- Pairs easily and quickly with the ClareOne panel

By making home technology simple, Clare provides exclusive benefits to integrators, builders, and homeowners. We offer innovative home automation solutions, wireless security, controllable lighting, and IP CCTV components. For more information, visit clarecontrols.com.