



ClareOne Door/Window Sensor with Shock Sensor

CLR-C1-DWSHK
CLR-C1-DWSHK-B

Intrusion



The ClareOne Door/Window Sensor with Shock Sensor provides an added level of intrusion protection for windows. The sensor functions as a magnetic contact opening, and also sends an alert to the ClareOne Panel when it senses a shock or impact on the window. Available in white or brown.

Specifications	
Compatible panel	ClareOne (CLR-C1-PNL1)
Transmitter frequency	433MHz
Encrypted	Yes
Operating gap	0.38 in (9.65 mm)
Transmitted indications	Tamper and low battery
Supervisory keep-alive	60-70 minutes
Shock sensitivity adjust	Yes
Battery type	(2x) CR2032
Battery life	8 to 10 years
Operating temperature	32°F to 120°F (0°C to 49°C)
Relative humidity	95% non-condensing
Dimensions (W x H x D)	2.25 x 1.0 x 0.50 in (57.15 x 25.4 x 12.7 mm)
Water resistant	No
Certifications	FCC: 15.109 Class B 15.231, Industry Canada: ICES-003, RSS-210

Performance Highlights:

- Adjustable shock detection sensitivity
- Effective with vertical or horizontal mounting
- Detects vibrations and impact
- Encrypted technology prevents alarm takeovers
- Pairs easily and quickly with the ClareOne panel

By making home technology simple, Clare provides exclusive benefits to integrators, builders, and homeowners. We offer innovative home automation solutions, wireless security, controllable lighting, and IP CCTV components. For more information, visit clarecontrols.com.