



ClareOne Glass Break Detector

CLR-C1-GB



The ClareOne Glass Break Detector is a ceiling or wall mount sensor that detects and communicates the sound of breaking glass. The detector provides a 20 ft maximum detection range, and can sense sound in a 360° pattern.

Specifications	
Compatible panel	ClareOne (CLR-C1-PNL1)
Transmitter frequency	433 MHz
Encrypted	Yes
Transmitted indications	Tamper and low battery
Supervisory keep-alive	60-70 minutes
Maximum detection range	20 ft (6 m) radius and 360° coverage pattern
Minimum detection range	4 ft (1.2 m)
Glass thickness	Up to 1/4" for plate, tempered, and laminated glass
Microphone	Omnidirectional 360°
Battery type	(2x) CR123A
Battery life	10 years
Operating temperature	32° F to 120° F (0° C to 50° C)
Relative humidity	0% to 95% RH non-condensing
Dimensions (W x H x D)	3.6 x 3.5 x 1 in. (91.5 x 88.9 x 25.4 mm)
Certifications	FCC: 15.109 Class B 15.231, Industry Canada: ICES-003, RSS-210

- 20 ft radius range and 360° coverage protects an entire room with motion sensor
- Two replaceable extra long-life lithium batteries
- Tamper protected
- Pairs easily and quickly with the ClareOne panel

By making home technology simple, Clare provides exclusive benefits to integrators, builders, and homeowners. We offer innovative home automation solutions, wireless security, controllable lighting, and IP CCTV components. For more information, visit clarecontrols.com.