



ClareVue In-Wall Receptacle

CVL-IWR-10



Specifications

General

Rating	120 VAC, 60 Hz
Z-Wave	Signal frequency 908.4/916 MHz
Z-Wave Outlet Load	600W incandescent, 1/2HP motor, or 1800W (15A) resistive
Total Max Load	Both outlets combined: 1800W resistive
Terminations	Requires line (hot), load, neutral, and ground. Traveler wire required for multi-pole installations
Operating Temperature	-32 to 104° F (-0° to 40° C)
Usage	Indoor only
Code Compliance	cUL Listed Complies with FCC and Industry Canada Regulations

This Z-Wave Plus certified ClareVue In-Wall Receptacle includes one Z-Wave outlet that can be remotely controlled using the ClareHome App. Toggle plugged in appliances and devices ON/OFF, set them on a schedule, automation, or include it in a scene.

- One Z-Wave controlled AC outlet
- One always-on pass-through outlet
- Remote and manual ON/OFF Z-Wave outlet
- Configure night LED ON/OFF in ClareHome App
- Can be added to scenes, schedules, and automations
- Z-Wave Plus certified
- White color
- Tamper resistant

By making home technology simple, Clare provides exclusive benefits to integrators, builders, and homeowners. We offer innovative home automation solutions, Class D amplifiers, media distribution, controllable lighting, and IP CCTV components. For more information, visit clarecontrols.com.