



ClareVue In-Wall Switch

CVL-IWS-10



Specifications	
General	
Rating	120 VAC, 60 Hz
Maximum Load	960W incandescent, 1/2 HP motor, or 1800W resistive
Z-Wave	Signal frequency 908.4/916 MHz
Terminations	Requires line (hot), load, neutral, and ground. Traveler wire required for multi-pole installations
Operating Temperature	-32 to 104° F (-0° to 40° C)
Usage	Indoor only
Code Compliance	cUL Listed Complies with FCC and Industry Canada Regulations

The ClareVue In-Wall Switch allows for manual and remote ON/OFF controls for lighting using the ClareHome App. The light switch can be paired with up to 4 ClareVue Accessory Switch-Dimmers. Included in the package are white and light almond color paddles.

- Remote and manual ON/OFF light control
- May be used with up to 4 accessory add-on dimmers
- Works with existing ClareVue 1, 2, and 3-gang cover plates
- Advanced configuration: LED status, invert switch (if unit is installed upside down)
- Requires neutral wire
- Configure night LED ON/OFF in ClareHome App
- Can be added to scenes, schedules, and automations



*Includes white and light almond color paddles.

By making home technology simple, Clare provides exclusive benefits to integrators, builders, and homeowners. We offer innovative home automation solutions, Class D amplifiers, media distribution, controllable lighting, and IP CCTV components. For more information, visit clarecontrols.com.