



ES-500-ICDVC-6

REAL PERFORMANCE FOR THE REAL WORLD

Premium components, engineered cross-overs, and clean aesthetics all combine to make this ES-500-ICDVC speaker a superior product. Merging both form and function, this in-ceiling speaker features stereo sound from a single speaker, offering the perfect solution when design dictates equipment.

SPECIFICATIONS

Woofer:	6½" Polypropylene Injection Cone, Nomex Spider & High Temp Voice Coil
Tweeter:	Two ½" Fabric Domes, Neodymium Motor, Ferrofluid Cooled
Power Handling:	80 Watts RMS, 200W Peak
Nominal Impedance:	8 Ohms
Frequency Response:	50 Hz - 20 kHz
Sensitivity -2.83 V / 1 Meter:	87 dB
Crossover Frequency:	4.3 kHz
Connector Type:	Gold Plated Push Terminals
Weight:	2.9 lbs.
Grill Type:	Aluminum Micro-Perf (Magnetic)
Mounting Depth:	3.4"
Finished Dimensions:	8.8" diameter, 3.8" deep

Designed to Perform

Combines the low frequency responsiveness of an injection-molded polypropylene woofer with fabric dome tweeters to deliver a smooth, natural high-frequency performance.

Built for Sound

Allows for multi-channel stereo sound from a single speaker. The angled tweeter array creates a wide separation of the stereo signal to fill the space, making it ideal for small areas and hallways where a traditional speaker pair would be aesthetically undesirable.

Engineered for Precision

Outstanding driver voicing and a specifically engineered 2nd order cross-over network ensure precise, responsive performance and separated the ES-500 from the pack.

Customized for Performance

Dual tweeter compensation switches for variable room environments allow these high-performance speakers to deliver every time.

Lifetime Limited Warranty

All Episode Speakers have a Lifetime Limited Warranty. This warranty includes parts and labor repairs on all components found to be defective in material or workmanship under normal conditions of use. This warranty shall not apply to products which have been abused, modified or disassembled. Products to be repaired under this warranty must be returned to SnapAV or a designated service center with prior notification and an assigned return authorization number (RA).