

500 Series 6in. In-Wall Speakers



ES-500-IW-6

SPECIFICATIONS

Woofer:	6 ¹ / ₂ " Polypropylene Injection
	Cone, Nomex Spider & High
	Temp Voice Coil
Tweeter:	1" Fabric Dome, Ferrofluid
	Cooled, Neo-Magnet Tweeter
Power:	110 Watts RMS, 275 Watt Peak
Nominal Impedance:	6 Ohms
Frequency Response:	50Hz - 20KHz
Sensitivity -2.83 V /	87.5 dB
1 Meter:	
Crossover Frequency:	3.8 kHz
Connector Type:	Gold-Plated Push Terminals
Weight:	3.9 lbs.
Grill Type:	Aluminum Micro-Perf Mesh
Finished Dimensions:	12" H x 8.6" W x 3.3" D

REAL PERFORMANCE FOR THE REAL WORLD

The perfect speaker for a variety of system needs, the ES-500-IW-6 is crafted with quality components and timbre-matched for seamless system design and performance levels that exceed anything else in its class. Ideal for background music, surround applications and mid-level listening rooms.

Designed to Perform

Top-notch components like a polypropylene woofer with Nomex spider, high temperature voice coil, and 1-in. fabric dome tweeter produce a clear, detailed sound and smooth, high-frequency response.

Engineered for Precision

Specifically engineered for precise and responsive performance, this speaker is equipped with outstanding driver voicing and a 2nd order crossover network to make dialogue and music sound its best.

Customized for Performance

No two rooms are alike. This speaker compensates for differences in sound absorption to provide clear, crisp audio in all corners of the room, and built specifically to reduce resonance and produce detailed sound without any distortion.

Lifetime Limited Warranty

All Episode Speakers have a Lifetime Limited Warranty. This warranty includes parts and labor repairs on all components found to be defective in material or workmanship under normal conditions of use. This warranty shall not apply to products which have been abused, modified or disassembled. Products to be repaired under this warranty must be returned to SnapAV or a designated service center with prior notification and an assigned return authorization number (RA).