



KIT-ECS-650-IC-4



KIT-ECS-650-IC-6

### Real Performance for the Real World

Get premium sound quality and performance in a discreet form factor with the 650 Commercial Series In-Ceiling Speakers. Installed directly into the ceiling, these products provide exceptional sound clarity and depth – and they won't take up any unnecessary space.

### Built for Sound

A two-way design gives these speakers incredible performance with dynamic highs and lows, meaning movies and music always sound their best.

### Engineered for Strength

These products feature high-temperature, UV-stabilized baffles that stand the test of time – and look great doing it. Plus each grille has extra reinforcement, so they won't fall out no matter how much bass is playing.

### Designed for Decor

Big sound is great – but large speakers cluttering up a space isn't. That's why these in-ceiling speakers are designed to provide exceptional sound that stays in the ceiling and out of the way.

### Specifications

		ECS-650-IC-4	ECS-650-IC-6
Woofer:		4" Vacuum-formed, Mica-Filled Polypropylene	6.5" Vacuum-formed, Mica-Filled polypropylene
Tweeter:		1" Silk Dome with Ferro-fluid cooled Neodymium Magnet	1" Silk Dome with Ferro-fluid cooled Neodymium Magnet
Power Handling:	RMS (w)	40w	60w
	Peak (w)	80w	120w
70v Tap Settings:		3.75w, 7.5w, 15w, 30w	7.5w, 15w, 30w, 60w
100v Tap Settings:		7.5w, 15w, 30w	15w, 30w, 65w
Low Impedance Bypass:		Yes	Yes
Recommended Min. Amp Power:		15W	15W
Nominal Impedance - Bypass Mode ( $\Omega$ ):		8 $\Omega$	8 $\Omega$
Frequency Response (-3dB):		65Hz - 20kHz	60Hz - 20kHz
Sensitivity (2.83v @ 1m):		84db	87db
Dispersion Angle:		130°	110°
Cutout Size:		7.9 in.	9.7 in.
Safety Agency Ratings:		UL1480, 2043	

### Lifetime Limited Warranty

All Episode Speakers have a Lifetime Limited Warranty. This warranty includes parts and labor repairs on all components found to be defective in material or workmanship under normal conditions of use. This warranty shall not apply to products which have been abused, modified or disassembled. Products to be repaired under this warranty must be returned to SnapAV or a designated service center with prior notification and an assigned return authorization number (RA).