WIREPATH

STRUCTURED WIRING



Plastic Makes Perfect

Wirepath Plastic Enclosures are more than a box - they allow your home and office to run smoothly every day. With ample space for proper equipment organization and UL-Listed ABS plastic for a consistently strong Wi-Fi signal, Wirepath delivers on the little things that make a big difference.

Strong Wi-Fi Signals

Molded with UL Certified ABS plastic, Wirepath Plastic Enclosures eliminate Wi-Fi interference for consistent internet speeds throughout the property, maximizing signal strength to maintain download speeds.

The Perfect Fit

With additional storage options, a space-saving door, and a low-profile power source, you'll have plenty of space for everything you need without cluttered equipment.

Smooth-Running System

Wirepath Plastic Enclosures are compatible with WattBox IP Power Conditioners, so if you have a problem with your system, your installer can resolve the issue without coming to your property, eliminating technician appointments and ensuring a quick resolution.





	WP-SW-PL-ENCL- 30-1PK	WP-SW-PL-ENCL- 30-5PK	WP-SW-PL-ENCL- 42-1PK	WP-SW-PL-ENCL- 42-5PK
Construction	UL Ceritified ABS Plastic Material			
Dimensions (W x H x D)	14.4" x 30" x 3.8"	14.4" x 30" x 3.8"	14.44" x 42" x 3.8"	14.44" x 42" x 3.8"
Sold As	1 pack	5 pack	1 pack	5 pack
Compatibility	Platform: WP-SW-PL-PLTFRM Shelf: WP-ONE-ENCL-SHELF	Platform: WP-SW-PL-PLTFRM Shelf: WP-ONE-ENCL-SHELF	Platform: WP-SW-PL-PLTFRM Shelf: WP-ONE-ENCL-SHELF	Platform: WP-SW-PL-PLTFRM Shelf: WP-ONE-ENCL-SHELF
Color	White (Paintable Surface)	White (Paintable Surface)	White (Paintable Surface)	White (Paintable Surface)
Knockout Size	1-3/4" OD	1-3/4" OD	1-3/4" OD	1-3/4" OD
Certifications	UL 1863 Certified	UL 1863 Certified	UL 1863 Certified	UL 1863 Certified
Operating Temperature	32°F - 125°F	32°F - 125°F	32°F - 125°F	32°F - 125°F







