


Specifications

| | |
|--|--|
| LCD Screen | 32-inch diagonal Color Active Matrix TFT LED LCD |
| Resolution | 1920 x 1080 1k (supports 4k downscaling) |
| Aspect Ratio | 16:9 |
| Blacklight Brightness - Surface Luminance, white | 1500 nits (cd/m2) |
| Contrast Ratio | tbd |
| Viewing Angle | tbd° x tbd° |
| Response Time | 8 milliseconds |
| TV formats | 2160p*, 1080p, 1080i, 720p, 720i, 480p, 480i * using hdmi only |
| Input Connectors: | |
| Tuner | Antenna/CATV (ATSC/QAM/NTSC) x1 |
| HDMI | HDMI Input x 2 (supports HDMI 2.0, HDCP 2.2, HDMI 1.4 & HDCP 1.4a) |
| Video Composite | Composite Video, L/R Audio Inputs x1 |
| Video Component | YPbPr plus Stereo Audio x1 (using 3.5mm to RCA adapter - not included) |
| PC | 15-pin D-sub VGA plus Stereo Audio |
| Ethernet | RJ45 - Single Cat5e/Cat 6 cable |
| HDBase-T | RJ45 - Single Cat5e/Cat 6 cable* |
| | *refer to detailed data sheet for supported resolutions, refresh, color depth and Cat5e/Cat 6 cable lengths. |
| Control Set | RS232 Serial, Discrete IR Control, Concealed rear IR Window, IP Control, OvrC |
| Audio Out | Digital Optical TosLink x 1 (fixed) Analog 1/8" headphone jack (variable) |
| Accessory DC Power Out | 5vdc @ 3.5amps 1.3mm power jack or usb type A jack 12vdc @ 3amps 2.5mm power jack |
| Speaker Output | 20-watt (10w x 2) Does not have internal speakers. Optional Speaker Bar not included. |
| Exterior | Powder-coated aluminum |
| Colors | Silver, Black and White |
| Input Power | 100-240 VAC, 50-60 Hz 1.9A |
| Operating Temp. | -24° to 122° F. (-31° to 50° C.) * |
| Non-op. Temp. (Off-mode with power applied) | -24° to 140° F. (-31° to 60° C.) The non-operating temperature feature requires power to be applied |
| Accessories Included | Water-resistant remote control |
| Dimensions | 30.35in W x 18.32in H x 4.49in D 771mm W x 466mm H x 114mm D |
| Weight | TV 41 lbs / 19 kgs Shipping tbd lbs (tbd kgs) |
| Residential Warranty | Two year, in-factory, parts and labor |
| Commercial Warranty | Two year, in-factory, parts and labor |
| Mount Pattern | 100mm x 100mm and 200mm x 200mm |

Model SB-P2-32-1K Pro2 HD Dimensions



Specifications are subject to change. 02/27/2020