


820  
SERIES



## Dimensions

Unit: mm



## Specifications

Product	LUM-820-IP-DM
Resolution	3840 x 2160
Shutter Speed	1s - 1/1000000s
Min. Illumination	0.015 lux, AGC ON; 0 lux with IR
Lens	2.8 - 12mm
Aperture	F1.4
Field of View	Horizontal: 97° - 32°/Vertical: 57° - 18°/Diagonal: 115° - 36°
IR Range	30 - 50m
Wide Dynamic Range	120dB
BLC	Yes
HLC	Yes
Digital Noise Reduction	Yes
Angle Adjustment	Pan: 0° - 345°/Tilt: 0° - 77°/Rotation: 0° - 345°
Video Compression	H.265+/H.265/H.264+/H.264
Main Stream	H.265(+): 3840 x 2160 30fps H.264(+): 3840 x 2160 30fps H.265(+): 3072 x 2048 30fps H.264(+): 3072 x 2048 30fps H.265(+): 2592 x 1944 30fps H.264(+): 2592 x 1944 30fps H.265(+): 2592 x 1520 30fps H.264(+): 2590 x 1520 30fps H.265(+): 2560 x 1440 30fps H.264(+): 2560 x 1440 30fps H.265(+): 2304 x 1296 30fps H.264(+): 2304 x 1296 30fps H.265(+): 1920 x 1080 30fps H.264(+): 1920 x 1080 30fps H.265(+): 1280 x 720 30fps H.264(+): 1280 x 720 30fps
Sub & Third Stream	H.264: 704 x 480 (30fps)
Fourth Stream	H.265: 1920 x 1080 30fps H.264: 1920 x 1080 30fps MJPEG: 1920 x 1080 30fps H.265: 1280 x 720 30fps H.264: 1280 x 720 30fps MJPEG: 1280 x 720 30fps
Audio & Alarm	Built-in microphone/Audio input & output/ 1 x Alarm input/1 x Alarm output
Storage	Built-in micro SD card slot/Up to 256GB
Reset Button	Yes
ONVIF Compliance NDA Compliant	Yes/Yes
Basic Event	Motion Detection/SD Card Full/SD Card Error
AI Event	Line Crossing/Region Intrusion/Region Entrance/Region Exit/Target Counting
AI Category	Human/Motor Vehicle/Non-motor Vehicle
Protection	IP67
Power Supply	DC12V/PoE
CVBS Output	Yes (Pigtail & Test Port)
Power Consumption	< 9W
Operating Temperature & Humidity	-22 F - 140F (-30 C - 60C) Less than 95% (non-condensing)
Dimensions & Weight	141mm x 100.2mm, 0.89KG (1.96lbs)
Certifications	ETL Listed, CE, FCC



## Summary

This low-profile, motorized, dome IP camera features 8MP resolution for 4K viewing. Featuring IR night viewing that eliminates over-exposure in dim settings and evenly illuminates the subject. With OvrC, on-site or remote configuration is a breeze, no longer requiring you to tediously navigate each camera's local UI. Adjust image settings in real-time, setup recordings, and more all via OvrC. Control System integration is always top of mind, and this camera is packed with features for Control4 along with many other popular control systems.

## Features

- AI-filtered events
- H.265+/H.265/H.264+/H.264/MJPEG coding
- Max.resolution: 8MP (3840 x 2160)
- ICR auto switch, true day/night vision
- 30-50m IR night view distance
- 2.8mm - 12mm motorized zoom lens
- Built-In Mic/1CH audio input
- Built-in micro SD card slot; up to 256GB
- DC12V/PoE power supply
- Support four streams
- IP67 and IK10
- Remote monitoring support via Luma View app

## Mounting Accessories (optional)

