

WIREFATH SURVEILLANCE CAMERA LINE OVERVIEW



		WPS-750-DOM-AH-BL WPS-750-DOM-AH-WH	WPS-750-BUL-AH-GR WPS-750-BUL-AH-WH	WPS-550-DOM-A-WH WPS-550-DOM-A-BL	WPS-550-BUL-A-GR WPS-550-BUL-A-WH	WPS-350-DOM-A-WH WPS-350-DOM-A-BL	WPS-350-BUL-A-WH WPS-350-BUL-A-GR
IMAGING	Image Sensor	1/3" Color Sony Super HAD II	1/3" Color Sony Super HAD II	1/3" Color Sony Super HAD II	1/3" Color Sony Super HAD II	1/3" Color Sony Super HAD II	1/3" Color Sony Super HAD II
	Resolution (TVLs)	650	650	600	600	550	550
	Lens	2.8 - 10mm Varifocal	3.7 - 12mm Varifocal	3.7 - 12mm Varifocal	3.7 - 12mm Varifocal	4 - 9mm Varifocal	4 - 9mm Varifocal
	IR Range	80 ft.	80 ft.	65 ft.	65 ft.	65 ft.	65 ft.
	Smart IR	Y	Y	Y	Y	Y	Y
	True Day / Night	Y	Y	Y	Y	N	N
TECHNOLOGY	OSD	Y	Y	Y	Y	N	N
	WDR	Super WDR	Super WDR	Digital WDR	Digital WDR	N	N
	DNR	3D DNR	3D DNR	2D DNR	2D DNR	N	N
	Minimum Illumination	0.03 Lux color 0.00003 Lux Sense-Up	0.03 Lux color 0.00003 Lux Sense-Up	0.01 Lux color 0 Lux IR on	0.01 Lux color 0 Lux IR on	0.01 Lux color 0 Lux IR on	0.3 Lux color 0 Lux IR on
	Sense-Up (Elec. Shutter)	Y	Y	N	N	N	N
	Highlight Compensation	Y	Y	Y	Y	N	N
	Auto Gain Control	Y	Y	Y	Y	N	N
	Back Light Compensation	Y	Y	Y	Y	N	N
HOUSING & POWER	White Balance	Y	Y	Y	Y	N	N
	Weather Rating	IP66	IP66	IP66	IP66	IP66	IP66
	Heater	Y	Y	N	N	N	N
	Vandal Resistant	Y	N	Y	N	Y	N
	RS485	Y	Y	Y	Y	N	N
	Power Source	Dual Voltage	Dual Voltage	Dual Voltage	Dual Voltage	12 VDC	12 VDC
	Dimensions	4.04" (H) x 5.91" (W)	9.96" (L) x 4.72" (H) with sun shade and bracket fully extended	4.04" (H) x 5.91" (W)	8.39" (L) x 3.82" (H) with sun shade and bracket fully extended	4.04" (H) x 5.91" (W)	8.39" (L) x 3.82" (H) with sun shade and bracket fully extended
MISC.	Available on Internet	N	N	N	N	N	N
	Warranty	5 year	5 year	5 year	5 year	5 year	5 year
	Ordering Ease	Easy	Easy	Easy	Easy	Easy	Easy
	Same Day Shipping	Y	Y	Y	Y	Y	Y
	Limited to CI Dealers	Y	Y	Y	Y	Y	Y

*Specifications subject to change without notice